

INTERFACE® FLAT CABLE

UL E486063
STYLE AWM 2651



INTERFACE® 28 AWG, 0.050" pitch extruded grey ribbon cable is for general purpose electronic interconnect and internal wiring applications. These are flexible with tear feature for termination to IDC connectors. These cables are UL approved and passes the VW-1 vertical Wire Flame Test.


PHYSICAL SPECIFICATIONS

Conductor	: 28 AWG
Material	: Tinned Copper
No. of Strands	: 7/0.127 mm
Insulation	: Grey PVC (Polyvinyl Chloride)
Pitch	: 0.050" ± 0.2mm
Avg. Tensile Strength	: 1,500 lbs/inch ²
Temperature Rating	: 105° C
Flammability Rating	: VW-1
UL AWM Style	: 2651
Packaging	: 30.5 Mtrs (100 Ft)
Core Size Available	: 10, 14, 16, 20, 26, 34, 40, 50, 60, 64

ELECTRICAL SPECIFICATIONS

Voltage Rating	: 300 V
Dielectric Strength	: Minimum 2 KV for 1 Minute
Conductor Resistance	: Maximum 237 Ω/km
Insulation Resistance	: Minimum 10 MΩ/km
Impedence	: 100 Ω
Capacitance	: 45 pF/m
Inductance	: 1.5 μH/m
Propogation Delay	: 4.2 ns/m

Construction Drawing



CALL FOR INTERFACE CONNECTORS



INTERFACE PLCC SERIES ICP1



INTERFACE BOX HEADER SERIES ICF2



INTERFACE FRC SERIES ICF1



INTERFACE PCB HEADER SERIES ICB1



INTERFACE D SUB SERIES ICD1



INTERFACE D SUB HD SERIES ICD2



INTERFACE PCB SOCKET ICB3



INTERFACE HOUSING SERIES ICB2 +
TERMINAL ICT1

Interface Connectronics Pvt. Ltd. # 85, Unit # 3, First Floor, V V Yoga Saurabha, S C Road Yeshwanthpur
Bangalore - 560 022 ☎ +91 80 233 747 72/ 3/ 4 📠 +91 97399 52969 📧 sales@icpl.co.in 🌐 www.icplindia.com

Connectors to Connectivity®

Interface®