



EFY GROUP
YOURS SINCE 1999

Facing problems in getting your favourite EFY Magazine in your area?

We can help you!



Electronics For You magazine is available on all top news-stands/outlets in India. If you are still facing problems in getting EFY magazine in your area, please call Akhilesh Yadav on **+91-8800295612** or drop an email at efycirc@efy.in. We will help you locate the nearest news-stand or arrange a copy at your doorstep.

electronics FOR YOU

South Asia's Most Popular Electronics Magazine

To become an agent of EFY Group publications, call Akhilesh Yadav on +91-8800295612 or write at efycirc@efy.in

its position dynamically but keeps on communicating with any other system in the Internet as long as link-layer connectivity is given is defined as MN. Home network (HN) is the subnet MN longs for. MN has its IP address with the home subnet. No mobile IP support is needed when MN communicates within HN. Foreign network (FN) is the subnet except HN. The current subnet is that in which MN node is visiting currently.

MNs are assigned two IP addresses. The first is called home address. Home IP address is a static address used to identify the end-to-end connection, and is used by MN when connected to its HN.

The second address is care of address (COA). It is not static. It is a dynamic address used for packet routing only and is used by MN by FN. CAO changes every time MN changes to a new sub-network. All IP datagrams sent to MN are delivered to COA, and not directly to the static IP address when MN is in FN.

There are two agents: foreign agent and home agent. These are known as mobility agents. These are mobile-IP-aware servers or routers that know where MN is actually connected. Home agent is HN's mobile IP agent, which has the responsibility of forwarding MN's packets to FN where MN is actually connected.

Foreign agent is responsible for delivering packets to the transient MN. It provides many services to MN during its visit to FN. It tracks COA, acting as the tunnel endpoint and forwarding packets to MN. Foreign agent is located in FN. It is the default router for MN when it is in FN. It also provides security services to MN.

Home agent is located in HN. It forwards IP packets to MN via COA. It maintains linked coordination between the home IP address of MN and its COA. A tunnel is established by home agent between itself and a reachable point (usually COA) for MN when it is in FN.

Working principle of mobile IP. The working principle of routing IP datagram in fixed Internet makes use of routers. Routers make use of IP address of IP datagram to route data from a source node to destination node.

IP address has two parts: network ID and host ID. Network ID identifies the sub-network on which the host is connected. Host ID is the host identification number.

Network ID is used by routers to move the datagram from one sub-network to another. Final router in the target sub-network moves the packet to a particular host based on host ID. MN communicates with another host or node on the Internet, mobile or not. The entire mobile IP process is transparent. MN is known to any other node or host by home address of MN wherever MN is physically present.

All packets between any other node or host and MN use MN's home address, regardless of whether MN is in HN or FN. COA is only used for communication with mobility agents and is never seen by any node or host while communicating with MN.

One of the important design goals of mobile IP is to make mobility possible without major changes to the large, existing installed base of IPv4, particularly routing infrastructure. The principle on which mobile IP works is based on three steps: data transfer, getting recognition (discovery) and registration.

Data transfer phase is made of encapsulation and tunnelling. It works as follows:

Packet from static node to MN. Any node or host (A) can send packet to MN (B), but it has to do so with the home address of MN. IP datagram will carry IP address of A as source and home address of B as destination address.

Incoming packet is intercepted by the home agent in HN. If MN is on home network, home agent delivers the packet locally. If MN is on FN, home agent forwards the packet to the foreign agent by the process of encapsulation and tunnelling. Home agent encapsulates the whole incoming packet into a new IP packet with B's COA as destination address and then transmits the encapsulated packet as one IP datagram. The method of using an outer different destination IP address is known as tunnelling.

Foreign agent on receiving the encapsulated packet strips off the outer IP header. This is called decap-