

COMPONENTS

High power amplifier

Aidin Technologies has designed and developed a state-of-the-art solid-state broadband gallium-nitride (GaN) high power amplifier for applications in radar, electronic warfare (EW) and communication. The power amplifier is designed to operate over UHF and L bands, providing simultaneously broadband or band-specific high power linear, CW and pulse applications.

Aidin Technologies Pvt Ltd
www.aidintech.com



DC/DC regulator

Allegro MicroSystems has launched ARG81800, a robust, ultra-low Iq, low EMI DC/DC regulator ideal for keep-alive supply applications. The device sets a new standard, introducing features that help engineers easily achieve tightening OEM standards, such as:

- Ultra-low quiescent current mode
- 150°C operating temperature, for demanding automotive or industrial operating conditions
- Pin open/short and component faults
- Unique EMC reductions achieved by incorporating spread spectrum frequency modulation (dithering) to a non-dithered external sync clock as well as providing a dithered clock output to be used for other converters in the system


Allegro MicroSystems
www.allegromicro.com

Radiation-tolerant FPGA

Developers of spacecraft electronics use radiation-tolerant (RT) field

programmable gate arrays (FPGAs) to create onboard systems that meet the demanding performance needs of future space missions, survive the brutal launch process and continue to operate reliably in the harsh environment of space. Extending its RT FPGA offering to bring these capabilities to emerging high-performance space applications, Microchip Technology has introduced RT PolarFire FPGA that is optimised to meet the most demanding requirements in spacecraft payload systems' high-speed data paths with the lowest possible power consumption and heat generation.

Microchip Technology Inc.
www.microchip.com



PCB connectors

Phoenix Contact brings a comprehensive range of innovative PCB connectors to cope up with all applications related to data, signal and power connection within and outside the device.

The range includes such connection solutions as panel feed-through, PCB terminals, pluggable terminals, ranging from 2.5mm to 20mm pitch with ratings up to 232A, 1000V, with a variety of connection technologies like screw, spring-cage, crimp, insulation displacement and piercecon.

Phoenix Contact India Pvt Ltd
adverts@phoenixcontact.co.in



DC-DC converter module

Artesyn Embedded Power, an Advanced Energy Industries Inc. (Nasdaq: AEIS) company, has announced its newest DC-DC converter module focused at gallium-nitride (GaN) radio frequency (RF)

power amplifier (PA) applications, the 500-watt AGQ500 series.



Housed in the industry-standard quarter-brick format, AGQ500 series offers greater than 95 per cent typical efficiency and a wide input range of 36 to 75 volts. The 50-volt nominal output model (AGQ500-48S50) is designed to support the growing use of GaN technology used in high-power wireless base station (BTS) deployments. This 50-volt model can deliver up to 10A output current.

Artesyn Embedded Power
www.artesyn.com

Analogue products

Designers can further reduce power consumption and solution size, while improving measurement accuracy, with three new industry-leading analogue products from Maxim Integrated Products. MAX6078A voltage reference IC, MAX16155 nanoPower supervisor and MAX16160 voltage monitor and reset IC achieve best-in-class performance for cloud infrastructure, the Internet of Things (IoT), intelligence-at-the-edge, on-device artificial intelligence (AI), as well as smart and emerging applications in consumer, communications, industrial and medical markets.

Maxim Integrated Products Inc.
www.maximintegrated.com

TRIAC thyristors

Littelfuse has announced an additional five series of high-temperature Alternistor TRIAC switching thyristors. The thyristors are designed for use as semiconductor switches in appliances and equipment powered by line AC voltages up to 250VRMS. Available

