

in five compact, surface-mount and through-hole packages, these components expand Littelfuse's TRIAC product line by making high 150°C maximum junction temperature devices available in 600V to 800V with ratings of 12A, 16A, 25A, 30A and 40A.

Littelfuse Inc.
www.littelfuse.com

TEST & MEASUREMENT

Signal generators

SIGLENT'S SSG3000X series of signal generators have a frequency range of 9kHz to 2.1GHz/3.2GHz. These provide normal analogue modulation such as AM, FM and PM. These also provide pulse modulation and pulse train generator.



In addition, when used with baseband generator, such as SDG6000X, these can generate IQ modulated signals. With their high accuracy and pure outputs, the SSG3000X series is the right choice for R&D, education and manufacturing.

Siglent Technologies Co. Ltd
https://int.siglent.com/

Solar clamp meter

CM65 is a rugged clamp meter designed to meet the challenges of solar installation, maintenance and repair. This clamp meter comes with quick-connect MC4 test leads that improve the accuracy and safety of DC voltage measurements on solar panel strings and inverters. With CM65, the user can validate AC output and inverter efficiency and then store readings to the internal memory. Share data wirelessly via METERLINK or monitor measurements live on a smartphone running FLIR Tools mobile app. Photovoltaic (PV) installers can trust CM65 as their go-to tool for accelerating and simplifying PV panel testing on new and existing solar panels.

Flir Systems India Pvt Ltd
www.flir.in



Surge generator

Mangal Instrumentation's surge generator is specially designed for LED lamps and luminaires, panel light and the like, to be used to appraise EMS capability of tested equipment on power ports and meets the standard requirements of IEC. It is used to assess the power cord and connect the internal switch to provide a common basis for switching the natural world and lighting caused by high energy disturbance.

Mangal Instrumentation
www.mangalinstruments.com



MISCELLANEOUS

AC/DC battery charger

Rebutor distributes AC/DC battery charger/UPS series EPS-200 that offers 200W and 48V, and allows monitoring and remote control. It is specially designed for applications for 4.0 Industry, the Internet of Things (IoT) and smart grids. Key features are:

- Full operation without battery
- Local monitoring with eight LEDs
- Remote monitoring with four alarm relays
- Monitoring and configuration via RJ45/Ethernet
- TCP/IP, DHCP, ICMP, HTTP, SNMP, LDAP protocols
- Embedded Web server
- Battery capacity test without heat dissipation
- 10kV AC isolation (20kV surges)
- Temperature sensor

Rebutor Electronics Pvt Ltd
www.rebutor.com



Switching power supply

MORNSUN released a new enclosed switching power supply series LMF100-20Bxx with active power factor correction (PFC). LMF100-20Bxx series

features universal input voltage range of 85V AC - 264V AC, accepts AC or DC input and the power factor is up to 0.98. In addition, its emissions meets CISPR32 CLASS B without extra components.

The new series also meets IEC/EN/UL62368, EN60335 and GB4943 safety standards. Protections of output short circuit, over-current, over-voltage and over-temperature are included. MTBF is more than 300,000h, and dimensions are ten per cent smaller than conventional products, which make this series ideal for industrial, civil, smart home and smart building applications.

Mornsun Guangzhou Science & Technology Co. Ltd
www.mornsun-power.com



Power module

The 20W ultra-small series power supply module is a small-volume, high-efficiency power module for customers designed by Hi-Link. It has the advantage of global input voltage range, low temperature rise, low power consumption, high efficiency, high reliability, high security isolation, etc. It has been widely used in smart home, automation control, communication equipment, instruments and other industries.

Rajguru Electronics (I) Pvt Ltd
www.rajguruelectronics.com



Door controller

COSEC VEGA FAX, an advanced door controller, has a TFT display with capacitive touchscreen interface to put events, news/message and other information. It can store up to 9600 fingerprint templates and 500,000 events. Its compact design with IP65 ratings is convenient for the demanding work environment of organisations.

