

COSEC VEGA FAX is an open system allowing integration with third-party hardware. Using auxiliary input and output ports, fire alarm and video surveillance systems can be connected without any need for external hardware modules. Motion sensors and relay devices can also be connected through these ports. The device has wireless connectivity options for employee time-tracking software application and access control terminals.

Matrix Comsec

www.matrixcomsec.com

ID security solution

Electronic identification documents (eID) are high in demand worldwide. To address the evolving needs of the market in a fast and flexible manner, Infineon Technologies has developed SECORA ID security solution. The latest addition to Infineon's SECORA family is certified and ready to be integrated into highly-secured eID documents. Furthermore, SECORA ID allows to run Java Card-based applications on smart cards and other small footprint devices, hence facilitating design, testing and deployment of eID solutions.

Infineon Technologies India Pvt Ltd

www.infineon.com

Ethernet transceiver

Analog Devices has released new robust, industrial Ethernet physical layer (PHY) products to help manufacturers address key Industry 4.0 and smart factory communication challenges surrounding data integration, synchronisation, edge connectivity and system interoperability. ADIN1300 is a low-power, single port Ethernet transceiver with industry-leading power and latency specifications primarily designed for time-critical industrial Ethernet applications up to gigabit speeds. As industrial automation increases adoption of Ethernet and pushes the boundaries of data rates, ADIN1300 is designed to operate reliably in harsh industrial conditions over extended ambient temperature ranges.

Analog Devices

www.analog.com

MCU ecosystem

Renesas Electronics has announced the first ten ready-to-use partner solutions that support the Renesas Advanced (RA) microcontroller (MCU) family of 32-bit Arm Cortex-M MCUs. RA MCUs deliver optimised performance and ease of use with Flexible Software Package (FSP) and partner building block solutions that work out-of-box to address a range of Internet of Things (IoT) endpoint and Edge applications.

Renesas Electronics Corp.

www.renesas.com

3D SPI system

Omron has released the new 3D SPI VP-9000 system used in PCB manufacturing process for the production of electric devices.



The solution complements its lineup of 3D-AOI and 3D-CT AXI systems, as well as flexible robotics solutions for personalised manufacturing. VP9000 can complete loop 3D inspection of a process with the opportunity to correct the excesses of a screen-printing process.

Key features are:

- Unique concept of 3D measurement combined with a 2D system
- Automatic warpage compensation
- Programming in three minutes
- Choice of resolutions by software
- Most advanced SPC software with detailed report function
- Inspection capacity up to 8900mm²/s
- M2M closed-loop function up and down-stream
- Used online or island position

Omron

<https://inspection.omron.eu/>

Lithium-ion charger

robu.in has introduced single-cell 18650 lithium-ion charger under SmartElex brand, SmartElex 1s Li-Ion Charger. Key features are:



- Offers 500mA charge current, and cuts off when finished.
- When battery voltage drops below Vmin, protection IC switches the load off to protect the cell from running at too low of a voltage
- Protects against over-voltage and reverse polarity connections
- Features status two LEDs, which indicates the Status of LED: charging, full charge or battery detects
- Has automatic battery-recharge feature

Macfos Pvt Ltd

www.robu.in

Sub-THz testbed for 6G research

National Instruments (NI) has announced a real-time sub-THz software-defined radio (SDR) for 6G research built on NI's mmWave transceiver system (MTS) and Virginia Diodes' (VDI) radio heads. Using VDI radio heads, frequency range of the MTS can extend into the sub-THz range. Because this testbed is built using SDRs and FPGAs, software can be upgraded and customised to meet a wide range of research needs and applications. Users can leverage existing software reference designs for channel sounding or wireless communications protocols to create a real-time testbed for 6G research.

National Instruments

www.ni.com

Wi-Fi+BLE chip

ESP-EYE is an ESP32-based development board that integrates a digital microphone, 8MB PSRAM and 4MB flash, while also providing an external 2MP camera. These features make the board ideal for applications relating to face detection, face recognition and speech recognition. Besides, the board can also support image transmission over Wi-Fi and debugging through a micro-USB port, which enables development of advanced artificial intelligence (AI) solutions. ESP32 is a single 2.4GHz Wi-Fi + Bluetooth combo chip designed with TSMC ultra low power 40nm technology.



Uchi Embedded Solutions

www.uchiembedded.co.in