

versus rotation, stray field immunity and highly adaptive performance.

Allegro MicroSystems
www.allegromicro.com

PCB connectors

Phoenix Contact brings a complete comprehensive range of innovative PCB connectors to cope with all applications related to data, signal and power connection solution within and outside the device. One can find various connection solutions such as panel feed-through,




PCB terminals, pluggable terminals, ranges from 2.5mm to 20mm pitch with ratings upto 232A, 1000V, with a variety of connection technologies like screw, spring-cage, crimp, insulation displacement and piercecon.

Phoenix Contact India Pvt Ltd
adverts@phoenixcontact.co.in

Current sensor

ROHM has announced the availability of the industry's smallest contactless current sensor, BM14270MUV-LB.



It achieves minimum power loss (no heat generation) in an ultra-compact size, making it ideal for industrial

equipment and consumer devices that detect operating conditions via current, including battery-driven drones, solar power systems and servers in data centres requiring high power.

ROHM Semiconductor India Pvt Ltd
www.rohm.com

TEST & MEASUREMENT

Cable tester

Total Phase advanced cable tester provides capabilities such as high-fidelity data throughput measurement, thorough continuity testing, IR drop for safe operation/reliability and e-marker verification. Rapid spot-checking of



cables, easy-to-understand reports and 100 per cent test coverage are available to casual, laboratory and production environments at a fraction of the price, setup time and labour.

GSAS Micro Systems Pvt Ltd
<https://gsasindia.com>

Clamp meter

FLIR CM275 clamp meter combines thermal imaging with electrical measurement into powerful inspection, troubleshooting and diagnostic tools. Through IR guided measurement (IGM), CM275 provides a reliable way to identify hot spots and overloaded circuits from a safe distance.

Key features include:

- Quick identification of issues with IGM, without contact with panels, cabinets or cluttered wires and cables that may present safety hazards
- Getting accurate amperage and voltage measurements and centre-point temperature readings; features a large display for data and image viewing
- Uploading and organising electrical measurements and thermal images, and sharing information with the team and file reports while in the field



FLIR Systems India Pvt Ltd
www.flir.in

Deep packet inspection solution

ipoque GmbH—a Rohde & Schwarz company—has announced the new R&S PACE 2 capabilities for the virtualised evolved packet core (vEPC) market. The high-performance deep packet inspection (DPI) product offers vEPC vendors comprehensive signatures for video streaming, breakthrough efficiency, enhanced NAT and tethering detection,

and flexible licensing.

R&S PACE 2 capabilities include:

- Extensive video streaming app signatures
- Extensive signatures for policy-bypass applications
- High DPI efficiency and scalability
- Improved NAT and tethering detection
- Custom Signatures

Rohde & Schwarz

www.rohde-schwarz.com, <https://ipoque.com>

Oscilloscope

Keysight Technologies has announced the 200MHz, 4-channel models of InfiniiVision 1000 X series oscilloscopes, providing professional-level measure-



ments and capabilities at an affordable price, including four-wire serial peripheral interface (SPI) decode and remote connection via local area networks.

The new oscilloscopes use the same user interface and measurement technology found in the higher performance Keysight InfiniiVision oscilloscopes. The intuitive front panel is easy-to-use and features built-in help enabling customers to quickly understand oscilloscope functions and improve overall test efficiency.

Keysight Technologies Inc.
www.keysight.com

Thermo anemometer

Kusam Electrical Industries has introduced a low-cost lightweight, portable digital thermo anemometer. It is used to check air-conditioning and heating systems, and measure air velocities, wind speeds, temperature, speed of the air of air blowers and fans, and so on. It has two simultaneous displays for temperature and speed of wind. It

