

- Signal demodulation: FM, LTE, digital signal
- Signal storage depth of 1Gbit for signal capture and analysis



- API library provided for secondary development
- 180mm × 50mm × 290mm compact size, weighing 1.8kg

Transcom Instruments

www.transcomwireless.com

Digital hardness tester

Metrix+ digital hardness tester Hardmaster-P is a portable hardness tester with 128x64 matrix LCD display showing all functions and parameters.



The readings, measured in HL, can be converted to all common scales of HV, HB, HRC, HRB, HRA and HS. By default, impact device D is used, and it supports seven optional types of impact devices.

The meter can be calibrated with the test piece and inbuilt software. Limit settings and alarms can be set for notifying users about out-of-range readings. HB values can be read out directly when D/DC impact device is used to measure cast steel work piece.

Minoo Impex

www.metrixinstrument.com

MISCELLANEOUS

Embedded SIM

Machine-to-machine communication in the Internet of Things (IoT) requires reliable data collection and uninterrupted data transmission. For taking full advantage of ubiquitous mobile networks, Infineon Technologies provides the world's first industrial-grade embedded SIM (eSIM) in a miniature wafer-level chip-scale package (WLCSP). Manufacturers of industrial machines and equipment ranging from vending machines and remote sensors to asset trackers can optimise the design of their IoT devices without compromising on security and quality.

Infineon Technologies India Pvt Ltd

www.infineon.com

Sensor fusion and tracking toolbox

MathWorks has introduced sensor fusion and tracking toolbox, which is available as part of release 2018b. The toolbox equips engineers working on autonomous systems in aerospace and defence, automotive, consumer electronics and other industries with algorithms and tools to maintain position, orientation and situational awareness. It extends MATLAB-based workflows to help engineers develop accurate perception algorithms for autonomous systems.

MathWorks

www.mathworks.com

People mobility management solution

Cosec Vyom is a people mobility management solution, based on cloud technology that allows users to use application, hardware and infrastructure as a service. Key features are:

- On-demand scalability in sync with organisation size
- No capex, maintenance and upgrades for IT
- Pay per usage
- Multi-level data encryption and protection
- Backup, archival, retrieval and migration

Matrix Comsec Pvt Ltd

www.matrixcomsec.com

Dotmatrix display

Electronic Assembly offers part of its LCD dotmatrix series in snap-in housings for fast, uncomplicated mounting. All displays are addressed via the serial RS-232C interface as standard. Optionally, control via RS-422 is also possible. Data transmission rates of 300, 1200, 2400 and 9600 baud are selectable.

Displays are ready for operation. All cursor controls, such as line feed, are executed automatically.



Snap-in variants are available for three text displays with 1x8, 2x16 and 4x20 characters.

Electronic Assembly GmbH

www.lcd-module.com

Touchscreen controllers

MXT2912TD-A, with nearly 3000 touch-sensing nodes, and MXT2113TD-A, supporting more than 2000 nodes, bring consumers the touchscreen user experience they expect in vehicles. The devices have been built upon Microchip's existing maX-Touch touchscreen technology. These also offer superior signal-to-noise capability to address the requirements of thick lenses, even supporting multiple finger touches through thick gloves and in the presence of moisture.



Microchip Technology Inc.

www.microchip.com

Component dispenser

The two-component dispenser ViscoDuo-P 4/4 allows individual configuration of each fluid component to reach a high-level result with excellent precision and high repeat accuracy. Each part of the two-component materials is dosed with high precision into the static mixer in compliance with the mixing ratio. The setting of the required mixing ratio is carried out through the adjustment of the speed ratio of dispensing tracks.



ViscoTec India Pvt Ltd

www.viscotec.de