

NEW PRODUCTS

COMPONENTS

AC/DC modules

RECOM's newest addition to its low-power AC/DC portfolio includes durable modules with full certifications for household and ITE applications.



Their 4kV isolation, 150 per cent peak power capability and -40°C to +90°C operating temperature make these suitable for a wide range of operating conditions.

The RAC04-K/277 series delivers an uncompromising 4W of continuous output power in harsh environments worldwide with up to 5000m altitude. The fully-encapsulated AC/DC modules are a complete solution without the need for external components.

RECOM Asia Pte Ltd

<https://recom-power.com>

CAN FD controller and transceiver

Texas Instruments has introduced an automotive system basis chip that integrates a controller and transceiver for controller area network with flexible data rate (CAN FD). Designed to meet high-bandwidth and data-rate flexibility needs of in-vehicle networks,



TCAN4550-Q1 uses serial peripheral interface (SPI) bus of almost any microcontroller to implement, with minimal hardware changes, a CAN FD interface or increase the amount of CAN FD bus ports in a system.

Texas Instruments

www.ti.com

Digital temperature indicators

Littelfuse has announced an expanded PolySwitch setP series of digital temperature indicators, designed to protect USB Type-C and USB power delivery charging cables from dangerous overheating. SETP0805-100-CC is

optimised for use in cables equipped with USB Type-C connectors at both ends.



Typical applications for SETP0805-100-CC are consumer electronics, primarily for mobile and wearable devices equipped with:

- USB Type-C cables (with a Type-C plug on each end)
- USB Type-C chargers (such as cables fixed or captive to a charger brick for laptops)

Littelfuse Inc.

www.littelfuse.com

Microcontroller

Nuvoton Technology is demonstrating the capability of FreeRTOS kernel support with NuMicro M2351 series. M2351 is one of the first Arm Cortex-M23-based microcontroller that has a preconfigured example that embedded developers can use to run FreeRTOS on the officially supported Armv8-M architecture. Amazon Web Services (AWS) released the latest FreeRTOS kernel that includes a pre-configured example project for Nuvoton NuMaker-PFM-M2351 evaluation board.

Nuvoton Technology Corp.

<https://m2351.nuvoton.com/>

DC-DC converter modules

Minmax Technology has introduced its MD family of isolated DC-DC converter modules, which offer very high power density of up to 63.5W/in³ for use in space-constrained designs. The 6W MDWI06, 8W MDWI08 and 10W MDWI10 are available with 4:1 input voltage ranges of 9V-36V or 18V-75V. The 8W



MDW08 and 10W MDW10 give a choice of three 2:1 input voltage ranges of 9V-18V, 18V-

36V or 36V-75V. All these series of converters are supplied in versions offering a fixed output voltage of 3.3V, 5V, 5.1V, 12V, 15V, 24V, $\pm 12V$ or $\pm 15V$.

Minmax Technology Co. Ltd

www.minmax.com

RX microcontrollers

Renesas Electronics has introduced RX72M group of RX microcontrollers (MCUs) featuring EtherCAT slave controller for industrial Ethernet communication. The new flagship product group for Renesas RX family offers a high-performance, single-chip MCU solution with large memory capacities for industrial equipment requiring control and com-



munication functions such as compact industrial robots, programmable logic controllers, remote I/O and industrial gateways.

Renesas Electronics Singapore Pte Ltd

www.renesas.com

RFID reader/writer OEM module

RRHFOEM05 is a ready-to-use multi-protocol HF RFID reader/writer OEM module with internal antenna. It operates on 13.56MHz and is compatible with the following standards: ISO15693/Tag IT/ISO18000-3/I-Code SLI, ISO14443A/Mifare and near field communication.

Key features include:

- Multiple LEDs for read and power
- Easy to integrate
- Ready to use

RapidRadio Solutions Pvt Ltd

www.rapidradio.co.in

Relays

Satronix introduces a wide range of digital analogue control solid-state