



relays with special embedded features intended for applications that demand exceptional reliability and accuracy. Their functions are as follows:

- MCU-based phase angle control (proportional controller)
- Burst fire control
- Soft start/soft stop
- Status monitoring
- Optional external contact for shut-down for protection

Satronix (I) Pvt Ltd

sales@satronix.net, satronix@gmail.com

DC/DC converters

TRACO POWER announces the release of the new TBA family of 1W and 2W



DC/DC converters in industry-standard SIP-7 package. The converters have been specifically designed to offer


a low-cost solution with no concessions on quality and lifetime. Enhanced features include integrated short-circuit protection circuit, higher I/O isolation and extended temperature range.

Traco Power

www.tracopower.us

RFID module

YHY521X is a highly integrated reader/writer for contactless communication at 13.56MHz. It supports ISO14443A/Mifare mode. It provides a robust and



efficient implementation of a demodulation and decoding circuitry for signals from ISO/IEC 14443A/Mifare-compatible cards and transponders. The digital part

handles the complete ISO/IEC 14443A framing and error detection.

Rajguru Electronics (I) Pvt Ltd

www.rajguruelectronics.com

TEST & MEASUREMENT

Vector network analysers

Anritsu introduces a 43.5GHz frequency option for its two- and four-port Shock-Line MS46122B, MS46322B, MS46522B and MS46524B vector network analysers (VNAs) with guaranteed specifications using Anritsu's Extended-K TM type connectors and components. The ShockLine family becomes the first VNA to support specified 43.5GHz functionality in a K-conductor environment, creating distinct cost-of-test and time-to-market advantages in high-frequency applications.

Anritsu India Pvt Ltd

www.anritsu.com



Thermal camera

FLIR T840 infrared (IR) camera is designed to help electric utility and other thermography professionals comfortably survey equipment both indoors or



out signs of failure all day long. Thanks to an integrated eyepiece viewfinder and a bright 10.2cm (4-inch) colour LCD display, T840 makes it easy to conduct inspections outside in bright, challenging lighting conditions. The 180-degree rotating lens platform and thoughtful ergonomic design allow T840 to help users diagnose hard-to-reach components in a variety of environments.

FLIR Systems India Pvt Ltd

www.flir.in

Vector signal transceiver

National Instruments has announced PXIe-5831 vector signal transceiver (VST) to further address time-to-market challenges for X-band, Ku-band and Ka-band radar and satellite communications (SATCOM) components and systems.



As the electromagnetic spectrum rapidly evolves to keep up with expanding requirements in areas like electronic battlefield and SATCOM, engineers need to reduce the time it takes to prototype, validate and test radar and communication systems at higher frequency bands. PXIe-5831 VST with modular millimetre-wave (mmWave) heads expands VST product family to provide frequency coverage up to 44GHz.

National Instruments

www.ni.com

Barometric pressure sensor

Infineon Technologies has introduced XENSIV DPS368, a miniaturised digital barometric pressure sensor capable of measuring both pressure and temperature. It offers an ultra-high precision of $\pm 2\text{cm}$, and a low current consumption for precise measurement of altitude, air flow and body movements. This makes DPS368 ideal for mobile applications and wearable devices offering activity tracking and navigation, among other functionalities.

Infineon Technologies India Pvt Ltd

www.infineon.com

Mini oscilloscope

MiniDSO is a handheld, portable, mini oscilloscope. Range, accuracy, bandwidth and resolution of the oscilloscope is perfect for everyday small- and medium-size projects. The device has a built-in waveform generator, which is useful for handy testing. It has open source hardware with ARM Cortex M3 core.

One advantage of the product is that, if it is not connected to USB, it has no ground reference, because of which it can be used like a multimeter on the high side, without creating a ground loop.

Macfos Pvt Ltd

Robu.in



AUDIO EQUIPMENT

Smart amplifier

As devices continue to shrink and customers demand ever sleeker products,