

Embedded Wireless and Low-Power Modules For IoT Applications

NEBULAE
DESIGN TO CONNECT



Smart Building

Smart Parking



Smart Health

Smart Agriculture



Smart Grid

Smart Manufacturing




SLS offers cost-effective, wireless NebuLink Nodes that are equipped with ultra-low power 32-bit RISC CPU with the clock speed of 1MHz-32MHz and processor with 32 kB RAM and 512 kB flash memory on-board. Integrated with Zigbee Pro Stack and Nebulae 6LoWPAN Stack makes the NebuLink Nodes versatile to any IoT application and are a great value for money.

Low
cost
and
Easy
to use



NLN 100a/b/c

STARTING FROM
INR 399*



NLN 100d

INR 699*



NLN 100e

INR 1190*

	NLN 100a/b/c	NLN 100d	NLN 100e
Frequency Band	ISM 2.4 GHz	ISM 2.4 GHz	863.25MHz to 875.65MHz 902MHz to 928MHz (OPTIONAL)
Tx Current Consumption	26.8mA@ +10dBm; 19.6mA@ +8.5dBm; 14mA @ +3dBm	104mA@ +19.88dBm	9mA@ +0dBm, 29mA@ + 14dBm
Rx Current Consumption	19.2mA@ +10dBm; 13A@ 0dBm	26mA@ +19.88dBm	11mA
Digital IO	5 to 20	Up to 20	Up to 20
Antenna Options	PCB Antenna, U.FL Connector, Wire Antenna, PCB Antenna or U.FL Connector	U.FL Connector	U.FL Connector

*Taxes as applicable

Contact us at +91 2692 232501(ext. 47) or Write to us at sales@nebulae.io



System Level Solutions

UK • INDIA • USA

www.slscorp.com



Scan QR Code or visit
www.nebulae.io