

AC/DC Converter

LHE Series			LDE Series	LM Series	LS Series	LI Series
Standard package		Low power consumption	Compact size	Enclosed	DIY type	DIN-Rail package
LHE(05-60)-20B • 5/10/15/20/25/40/60 Watts • 85-264VAC • 3000/4000VAC Isolation • Single output	LHE(05-20)-20A/C/D • 5/10/15/20 Watts • 85-264VAC/100-370VDC • 4000VAC Isolation • Multiple outputs	LH15/25-20BxxMU • 15/25 Watts • 85-264VAC/100-370VDC • 4000VAC Isolation • Meet EN60601-1, ANSI/AAMI ES60601-1(2"MDPP) Standards	LDE(03-20)-20B • 3/5/6/10/15/20 Watts • 85-264VAC/100-370VDC • 4000VAC Isolation	LM(35-350)-20B • 85-264VAC Input • 35/50/75/100/150/200/350 Watts • Single output • Isolation up to 4000VAC	LS01/03/05-15B LS05/08/10-13B • 1/3/5/8/10 Watts • 85-305VAC/85-264VAC • 3000VAC Isolation • Efficiency up to 79%	LI240-10B • 240 Watts • 3000VAC Isolation • Remote on/off • Active PFC
LH05/20-13B • 5/20 Watts • 80-305VAC/100-430VDC • 3000VAC	LHE(10-40)-23B • 10/15/25/40 Watts • 80-305VAC/100-430VDC • 4000VAC			LM(35-350)-22B • 165-264VAC Input • 35/50/75/100/150/200/350 Watts • Single output • Isolation up to 4000VAC	Three phase AC/DC power supply LS03-16B LS05-26B • 3/5 Watts • 90-528VAC/100-745VDC • 4000VAC Isolation • Output short circuit protection	LI(30-100)-20BxxPR2 LI120-20BxxR2 • 30/60/100/120 Watts • 4000VAC Isolation • 85(90)-264VAC
			LDE02/05/10-23B • 2/5/10 Watts • 85-305VAC/120-430VDC • 4000VAC Isolation	LM(35-100)-10C/D • 85-264VAC Input • 35/50/75/100 Watts • Dual/Triple outputs • 3000VAC Isolation	LSC15-26M • 15 Watts • 45-528VAC/65-745VDC • 4000VAC Isolation	LO Series Open frame LO(03-65)-10B • 3/5/15/30/45/65 Watts • 85-264VAC • 3000VAC Isolation

Transceiver Module

Transceiver Module With built in isolated DC/DC Converter	
CAN	RS485
TD321/521DCAN TD321/521DCANH • 110 Nodes • Single output • Rate: 5K-1Mbps, 40K-1Mbps • TDx210CANx: Two-port isolation (3000VDC) • TDx220CAN: Two-port isolation (2500VDC) / Channel isolation (1500VDC)	TD321/521D485 TD321/521D485H(-A/E) • 64-256 Node • Single output • Rate: 0-19.2Kbps/0-500Kbps/ • 0-200Kbps options • Two-port isolation 3000VDC (input and output are mutually isolated)
TD301/501MCANFD • 110 Nodes • Single output • Rate: 40K-5Mbps • Compact size	TD321/521S485 • 64 Nodes • Compact size, SMD Package • Rate: 0-19.2Kbps • 2500/3000VDC Isolation
TD301/501CANHE • 110 Nodes • Single output • Rate: 20K-1Mbps • High surge protective type	TD322/522D485H-A • 32 Nodes • Dual outputs • Rate: 0-120Kbps
TD321/521SCAN • 110 Nodes • Compact size, SMD package • Rate: 5K-1Mbps • 3000VDC Isolation	TD331/531S485 TD331/531S485H(-A/E) • Small SMD12 size • Rate: up to 500Kbps
TD322/522DCAN • 110 Nodes • Dual outputs • Rate: 40K-1Mbps	RS232 TD531/331S232H • Small SMD12 size • Rate: 115200bps • Meet EIA/TIA-232-F standard
TD331/531SCANH/FD • Small SMD12 size • Rate: 5Mbps • 110 Nodes	

AC/DC converter Integrated CAN/485

TLA03/05-03KCAN

 • 110 Nodes
 • 4000VAC Isolation
 • 85-305VAC/100-430VDC
 • Rate up to 1Mbps
 • Rate: 5K-1Mbps

TLA03/05-03K485

 • 128 Nodes
 • 4000VAC Isolation
 • 85-305VAC/100-430VDC
 • Rate up to 500Kbps
 • Rate: 0-500Kbps

IGBT Driver

IGBT Driver

QC962-8A

 • Built-in high CMRR opto-coupler (CMRR: Typ.30kV/μs, Min:15kV/μs)
 • High isolation(3750VRMS/min)
 • Short-circuit and output fault function

QP12W08S-37(A)

 • Built-in DC/DC isolation power supply
 • Isolation:3750VAC
 • Switching frequency up to 20kHz
 • Short-circuit and output fault function

White Goods Power Supply

LD03-20BxxWG

 • 3 Watts
 • 4000VAC Isolation
 • 0.2W Stand-by power consumption
 • EN60335 approved

LO15/30-10B

 • 15/30 Watts
 • 85-264VAC
 • 3000VAC Isolation
 • Meet requirements of White Goods

3-200W Wide Input Voltage DC/DC Converter R3 Series

High performance at an affordable price

- Efficiency up to 94%
- 2:1/4:1 Wide input range
- Stand-by power consumption as low as 0.1W
- Isolation: 1500/2250/3000/6000VDC

Recommended

One-stop solutions of power supplies

MORNSUN Power

No.5, Kehui St.1, Kehui Development Center, Science Ave.,
Guangzhou Science City, Huangpu District, Guangzhou

Tel: 020-38601850 Fax: 020-38601272

Email: info@mornsun.cn

www.mornsun-power.com

MORNSUN America, LLC

Tel: +1 (978) 567 9610 / 293 3923
Email: sales@mornsunamerica.com
www.mornsunamerica.com

MORNSUN Power GmbH

Tel: +49 (0) 89/693 350 20
Email: info@mornsunpower.de
www.mornsunpower.de



mornsun website