

DC/DC Converter

Fixed input voltage			Wide input voltage				
≤1 Watt		2 to 3 Watts	1 to 3 Watts	6 to 40 Watts			
SMD	F_XT-W2R2/R3 • 0.25 Watt • 3000VDC Isolation • Continuous short circuit protection	A/B/F_XT-1WR2/R3 E_XT-1WR2/1WR3 • 1 Watt • Unregulated dual/single outputs • Continuous short circuit protection	B/F_XT-2WR2 • 2 Watts • Unregulated dual/single outputs • 1500/3000VDC Isolation	WRA/B_S-1WR2/3WR2 • 4.5-9, 9-18, 18-36, 36-75 VDC Input • 1500/3000VDC Isolation	VRB_LD-15WR3 VRA/B_LD-20WR3 • 9-18, 18-36, 36-75VDC Input • 1500VDC Isolation	VRB_LD-40WR3 • 18-36, 36-75VDC Input • 1500VDC Isolation • Efficiency up to 91% • With heat sink	URA/B1D_YMD-6WR3 • 40-160VDC Input • Efficiency up to 89% • 2250VDC Isolation
	IB_XT-W75R3 • 0.75 Watt • Regulated single output • 1500VDC Isolation • Continuous short circuit protection	IB_XT-1WR2 IF_XT-1WR2/R3 • 1 Watt • Regulated single output • 1500/3000VDC Isolation • Continuous short circuit protection		WRE/F_P-3WR2 • 4.5-9, 9-18, 18-36, 36-75 VDC Input • 3000VDC Isolation	URE/F/H_P-6WR3 • 9-36, 18-75VDC Input • 3000/6000VDC Isolation	URB_S-6WR3/10WR3 • 9-36VDC Input • Single output • No-load power consumption as low as 0.12W	URB_ZP-6WR3 URA/B_ZP-10WR3 • 9-36, 18-75VDC Input • Dual/single outputs • 1500VDC Isolation
	A/B/E/F_S-1WR2/R3 • 1 Watt • Unregulated single output • Continuous short circuit protection	B_LS-1WR2/R3 • 1 Watt • Unregulated dual outputs • Continuous short circuit protection	A/B/E/G/H_S-2WR2 • 2 Watts • Unregulated dual/single outputs • 1500/3000VDC Isolation	WRA/B_ZP-3WR2 • 4.5-9, 9-18, 18-36, 36-75 VDC Input • 3000VDC Isolation	URB1D_LMD-10WR3/15WR3/20WR3 • 40-160VDC Input • Single output • 2250VDC Isolation	URA/B_LD-20WR3/30WR3 • 9-36, 18-75VDC Input • 1500VDC Isolation • Efficiency up to 90%	URB1D_LD-20WR3 URE1D_LD-20WR3 URF1D_LD-40WR3 • 40-160VDC Input • 2250VDC Isolation
IB_S-W75R3 • 0.75 Watt • Regulated single output • Continuous short circuit protection	IB_LS-1W/1WR3 IF_S-1W/1WR3 • 1 Watt • Regulated single output • Continuous short circuit protection	B/F_S-3WR2 • 3 Watts • Unregulated single output • 3000VDC Isolation	URB_MT-3WR3 • 9-36, 18-75VDC Input • 1500VDC Isolation • Efficiency up to 84%	URE/F_LP-10WR3 URF_LP-20WR3 • 9-36, 18-75VDC Input • 3000VDC Isolation • Efficiency up to 88%	VRB_J(M)D-T-6W URB_J(M)D-T-10W/15W • 9-36, 18-75VDC/9-18, 18-36VDC Input • 1500VDC Isolation	URB_YMD-6WR3/10WR3/15WR3/20WR3 URA_YMD-20WR3 • 40-160VDC Input • 2250VDC Isolation	
F_N-1WR3 • 1 Watt • Continuous short circuit protection • International standard pin-out		A/B/E/F_D-2WR2 • 2 Watts • Unregulated single & dual outputs • 1500/3000VDC Isolation	75 to 200 Watts URF_QB-75W/100W/150W/200WR3 • 9-36, 18-75VDC Input • Efficiency up to 94% • 2250VDC Isolation			Non-isolated K78L-500R3/1000R3 • Open frame • Efficiency up to 95% • Ultra low no-load power consumption • Short circuit protection	
Photovoltaic Power Supply PV10-27C PV15-29C PV45-29D PV60-27D • 10/15/45/60 Watts • Dual/triple outputs		DC/DC Converter for IGBT Driver QA01/02/03/04 • ±10% Input • Ultra low isolation capacitance • 3000VAC Isolation • No-load operation allowed			K78xxM-1000R3 • Efficiency up to 96% • Low no-load power consumption • Short circuit protection		
PV(05-200)-27B • 5/10/15/40/120/200 Watts • 100-1200VDC input • 4000VAC isolation • Single output	PV(15-200)-29B • 15/40/200 Watts • 200-1500VDC input • 4000VAC isolation • Single output	QAW01/02 • 9-18, 18-36VDC Input • 0.24-4.8 Watts • 3000VDC Isolation • Output over-voltage Protection	QA01C • ±10% Input • 3500VAC Isolation • Designed for SiC Driver	QA152D • ±10% Input • 3500VAC Isolation • Designed for SiC Driver	K78T-500R3/1000R3 K78_JT-500R3 • Efficiency up to 95% • Low no-load power consumption • Short circuit protection	K78-500/1000/2000R3 K78_W-500R3 • Efficiency up to 96% • Pin-out compatible with LM78XX linear regulators • Short circuit protection	
Railway Power Supply URB1D_YMD-6WR3 URB1D_LMD-10/15/20WR3 URB_URE1D_LD-20WR3 URF1D_LD-40WR3 • 6-40 Watts • 40-160VDC Input • Single output • 2250/3000VDC Isolation		URF1D_QB-50/75WR3 URF1D_QB-100/150/250WR3 • 50/75/100/150/250 Watts • 43-160VDC Input • 3000VAC Isolation • Meet EN50155 standard	Optional Mountings PCB Mounting				
			 DIN-Rail Mounting				
			 Chassis Mounting				

For more information, please visit www.mornsun-power.com



Position:
Regional Field Application Engineer

Location:
Delhi, Mumbai, Hyderabad

Required to have:
Strong knowledge and experience in AC/DC and DC/DC SMPS design, testing, analysis and application.

Mail your CV to: sales820@mornsun.cn



mornsun website