

a tester for measuring RF TRx characteristics of equipment with built-in WLAN IEEE802.11a/b/g/n/ac functions (2.4GHz and 5GHz bands). It supports



network mode to communicate with the EUT using standard WLAN protocol messaging (WLAN signalling) for performing TRx measurements.

Anritsu India Pvt Ltd
www.anritsu.com

Digital coating thickness gauge

Metrix+ digital coating thickness gauges—coat gauge F xL and coat gauge FN xL—are a part of newly-introduced coat gauge xL series. These have integrated probes for measuring the thickness of coatings on ferrous and non-ferrous substrates using the principle of electromagnetic induction and eddy current.



minoo Impex
www.metrixinstrument.com

DC power supply

With the development of the battery, from the original 1.5V dry battery to the power battery up to 800V/50kW, there are three types traditional test solutions: DC power supply + high power resistance box, DC power supply + energy-consuming electronic load and DC power supply + regenerative load. ITECH's solution uses a bidirectional DC power supply (IT6000C) to carry out the tests. IT6000C combines the function of a bidirectional power supply and a regenerative electronic load.

AARJAY International Pvt Ltd
www.itechate.com

MISCELLANEOUS

Membrane dispensing valve

DOPAG's membrane dispensing valves are designed for care-free dispensing of

low to high viscosity, filled or unfilled, abrasive or chemically-reactive 1K fluids. Part of their structure is an integrated membrane that separates the pneumatic and the metering parts of the valves. As a result, only the valve head and membrane come in contact with the material, while the material passageway can be easily flushed, if necessary. Material dripping after shot completion is effectively prevented by the snuff-back mechanism.

DOPAG India Pvt Ltd
www.dopag.in



Liquid crystal display

The compact LCD display DOGS164-A by Electronic Assembly, designed especially for low-power handheld devices, is only 2mm thick. With external compact



dimensions of 40mm x 33mm, it offers space for four lines with 16 characters, each 3.2mm high. Optionally, users can also select 2 x 16 double-size characters or a mixed display with one large and two small lines.

Electronic Assembly GmbH
www lcd-module.com

Phone system

Matrix Eternity NENx is a small yet powerful phone system for small businesses, offering advanced features and



functionalities as available with enterprise-grade IP-PBXs. Based on modular architecture and state-of-the-art design, Eternity NENx provides connectivity to CO (FXO), GSM/3G and VOIP networks

from a single platform. Range of phone options such as analogue, IP and mobile extensions provides flexibility to communicate from anywhere and at any time. Furthermore, Eternity NENx offers integrated voicemail system, multiple auto-attendants and Web-based remote management.

Matrix Comsec Pvt Ltd
www.matrixtelesol.com,
www.matrixcomsec.com

Software update

Pulsonix has announced the release of Pulsonix version 10.5, with over 30 new enhancements based on user requests



from professional PCB designers. Pulsonix 10.5 release includes new 3D viewing options for component and enclosure transparency, lighting and clash markers, and component-to-component distance measurements.

Pulsonix
www.pulsonix.com

Reference designs

Texas Instruments has introduced fully-tested reference designs for battery management and traction inverter systems, along with new analogue circuits with advanced monitoring and protection features to help reduce carbon-dioxide emissions and enable hybrid electric vehicles and electric vehicles (HEV/EVs) to drive farther and longer.

Scalable across six to 96-series cell supervision circuits, the new battery management system reference design features the advanced BQ79606A-Q1 precision battery monitor and balancer. Engineers can get their automotive designs to market quickly using the reference design, which implements the battery monitor in a daisy chain configuration to create a highly-accurate and reliable system design for 3-to 378-series, 12V up to 1.5kV lithium-ion battery packs.

Texas Instruments Inc.
www.ti.com