

are you ready for the FUTURE?



RP Lidar | Benewake

Wide variety of sensors available

- Field of view of 13° to 360°
- Detection range 6m to 180m
- Infrared 3D Lidar to solid state Lidar



GET IT ON
Google Play



Visit Now to explore 3000+ Amazing Products

are similar to a safe, where companies store important documents and secret files.

Getting started with Google Cloud IoT Core secure authentication

A different approach to certificate-based mutual authentication is proposed with the ATECC608a secure element combined with Cortex-M0+ ATSAM21 and WINC1500 Wi-Fi network controller connected to Google Cloud IoT Core. This implementation uses a JSON Web-based token (JWT). When a Message Queuing Telemetry Transport (MQTT) connection occurs, CryptoAuthLib hosted in ATSAM21 generates the JWT token.

A part of the token is hashed and presented to ATECC608a, which provides an ECDSA signature of the token using the private key hosted in the



Using Google Cloud IoT Core

secure element. This is appended to the rest of the token in the MQTT message in the MCU. The signed token is placed in the password location of the

MQTT message, which is then presented to Google Cloud IoT Core.

Previously, the corresponding public key is loaded in Google Cloud IoT Core account, which verifies that the signed token is genuine. TLS and TCP/IP stacks are hosted in WINC1500, enabling the smallest MCUs to be connected securely.

In-manufacturing secure provisioning processes, like the one from Microchip with ATECC608a CryptoAuthentication device, coupled with Just in Time Registration (JITR) from AWS IoT or JWT-based authentication on Google IoT Core platform, offer a great way to

ensure IoT security. With such end-to-end IoT security solutions, Industry 4.0 security can be ensured to successfully drive safe and efficient growth. **EFY**