



Wireless Control - Infinite Possibilities

Sub-1GHz RF Tx/Rx IC & SoC Flash MCU

Holtek's new unidirectional Tx/Rx independent RF ICs and SoC Flash MCUs are provided with a range of options which enable them to be used in a wide range of product designs. All are compliant with the ETSI and FCC specifications. These new devices will see excellent use in unidirectional Tx/Rx wireless control applications, such as wireless control systems, home entertainment products, security protection equipment, smart household appliances, etc.

Tx IC/SoC MCU

- Supports OOK/FSK modulation modes with programmable, transmission power
- Single crystal, 315/433/868/915MHz Sub-1GHz ISM frequency bands
- Tx device has integrated fuse for transmission parameter storage, providing simplified peripheral requirements
- RF transmission characteristics are compliant with safety requirements
- Provide professional RF technology and product support

- Original super-generative Rx+MCU SoC architecture for simplified design and control
- High sensitivity OOK receiver capacity (-97dBm) with receiver power consumption less than 4mA at 5V
- Supports 315 MHz and 433 MHz Sub-1GHz ISM frequency bands
- Receiving rate: 5ksps Symbol Rate (Typ.)
- Provides Holtek Tx/Rx matching solutions

Rx IC/SoC MCU

