



models; LPS operates in the range of 0.5 to 5 bar, while HPS operates in the range of 2 to 25 bar. A microswitch of 250V, 16A rating is used, which is capable of running motor pump. The switches can operate in the temperature range of -10°C to 80°C . Hysteresis is 10-30 per cent of set value.

Falcon Engineering

contact@falconengineering.in

TEST & MEASUREMENT

Digital insulation tester

MECO-G has introduced two new multi-range insulation testers. Model R-DT903A has three voltage ranges (250V/500V/1000V) and 0-200M Ω to 2000M Ω . Model R-DT945K also has three voltage ranges (1000V/2500V/5000V) and 10M Ω to 200G Ω (auto). Both



models have AC voltage range to measure 0V AC to 600V AC. Readings can be frozen with data hold function. The instruments can operate with 1.5V AA batteries or AC mains adaptor. These have a large LCD display with 33mm digit height. Backlight facility is also provided.

Goliya Instruments Private Ltd

www.goliyainstruments.com

Vector network analyser

Rohde & Schwarz introduces R&S ZNA, a new generation of high-end vector network analyser offering outstanding RF performance and a unique hard-



ware concept that simplifies measurement configuration. Its excellent measurement stability and trace noise enable users to perform demanding measurements on active and passive components and modules. Thanks to its innovative, DUT-centric approach, the world's first purely touch-operated vector network analyser reduces configuration times to a minimum.

Rohde & Schwarz

www.rohde-schwarz.com

INTERNET OF THINGS

Sensor development kit

ON Semiconductor has introduced RSL10 sensor development kit, designed to provide engineering teams with a comprehensive platform for developing Internet of Things (IoT) applications with cutting-edge smart sensor technology, enabled by Bluetooth Low Energy radio. RSL10 brings together the highly integrated RSL10 system-in-package (RSL10 SIP) with a range of advanced low-power sensors from Bosch Sensortec. The platform provides nine degrees of freedom detection and environmental monitoring, including ambient light, volatile organic compounds, pressure, relative humidity and temperature. An ultra-low noise digital microphone is also included, along with a user-programmable RGB LED, three programmable push-button switches and 64kb EEPROM.

ON Semiconductor

www.onsemi.com

IoT cloud

Arduino has introduced an IoT cloud as part of its professional IoT strategy. Targeted at developers, system integrators and maker hobbyists, Arduino IoT cloud is an easy-to-use IoT application platform that enables users to develop and manage IoT applications that solve real-life problems. Introduction of this new platform builds on Arduino's mission of making complex technology simple enough for anyone to use.

Arduino

www.arduino.cc

LoRa security solution

Microchip Technology, in partnership with The Things Industries, has announced the industry's first end-to-end security solution that adds secure, trusted and managed authentication to LoRaWAN devices at a global scale. The solution brings hardware-based security to the LoRa ecosystem, combining the MCU- and radio-agnostic ATECC608A-MAHTN-T CryptoAuthentication device with The Things Industries' managed servers and Microchip's secure provisioning service.

Microchip Technology Inc.

www.microchip.com

Security solution

Designers of IoT devices now have a smarter and more secure way to protect stored, sensitive information with the highly integrated MAX36010 and MAX36011 single-chip security supervisors from Maxim Integrated Products. These security solutions make it easier for designers to implement robust tamper detection, cryptography and secure storage while safeguarding sensitive information via logical and physical protections, without having to be security experts themselves.

Maxim Integrated Products Inc.

www.maximintegrated.com

MISCELLANEOUS

Communication server

Matrix PRASAR UCS, an enterprise unified communication server, connects internal and external decision-makers at multiple locations for effective communication and real-time collaboration. It enables enterprises to enhance business processes by unifying communication mediums to simplify the daily workflow and increase their response time. Being a pure IP solution, PRASAR UCS is a single-box solution, scalable up to 2100 users, as per future communication needs of an organisation.

Matrix Comsec

www.matrixcomsec.com



Screen printer

X5L vision screen printer manufactured by Inotis Co. Ltd is a fully-automated high-speed printer with a motorised three-stage conveyor system, which ensures reduction in the waiting time for PCB transfer. The printer has a multi-point PCB clamping block that provides edge clamping control for board holding to obtain best printing quality for fine-pitch devices. A PCB pushdown unit is used for large PCBs to prevent warpage.

Kyoritsu Electric India Pvt Ltd

www.kyoritsuelectric.com

