

DC/DC Converter

Fixed input voltage

≤1 Watt

2 to 3 Watts

SMD Package

F_XT-W2R2/R3

CE

- 0.25 Watt
- 3000VDC Isolation
- Continuous short circuit protection

A/B/F_XT-1WR2/R3
E_XT-1WR2/1WR3

CE CB

- 1 Watt
- Unregulated dual/single outputs
- Continuous short circuit protection

B/F_XT-2WR2

CE

- 2 Watts
- Unregulated dual/single outputs
- 1500/3000VDC Isolation

IB_XT-W75R3

CE

- 0.75 Watt
- Regulated single output
- 1500VDC Isolation
- Continuous short circuit protection

IB_XT-1WR2
IF_XT-1WR2/R3

CE

- 1 Watt
- Regulated single output
- 1500/3000VDC Isolation
- Continuous short circuit protection

SIP Package

A/B/E/F_S-1WR2/R3

CE CB

- 1 Watt
- Unregulated single output
- Continuous short circuit protection

B_LS-1WR2/R3

CE

- 1 Watt
- Unregulated dual outputs
- Continuous short circuit protection

A/B/E/G/H_S-2WR2

CE CB

- 2 Watts
- Unregulated dual/single outputs
- 1500/3000VDC Isolation

IB_S-W75R3

CE

- 0.75 Watt
- Regulated single output
- Continuous short circuit protection

IB_LS-1W/1WR3
IF_S-1W/1WR3

CE CB

- 1 Watt
- Regulated single output
- Continuous short circuit protection

B/F_S-3WR2

CE

- 3 Watts
- Unregulated single output
- 3000VDC Isolation

DIP Package

F_N-1WR3

CE

- 1 Watt
- Continuous short circuit protection
- International standard pin-out

A/B/E/F_D-2WR2

CE CB

- 2 Watts
- Unregulated single & dual outputs
- 1500/3000VDC Isolation

Wide input voltage

1 to 3 Watts

6 to 40 Watts

WRA/B_S-1WR2/
3WR2

CE

- 2:1 input
- 1500/3000VDC Isolation
- Dual/single outputs
- Remote on/off

VRB_LD-15WR3
VRA/B_LD-20WR3

CE CB

- 2:1 input
- 1500VDC Isolation
- No-load power consumption as low as 0.12W

VRB_LD-40WHR3

CE

- 2:1 input
- Single outputs
- 1500VDC Isolation
- Efficiency up to 91% With heat sink

URA/B1D_YMD-6WR3

CE

- 4:1 input
- Efficiency up to 86%
- 2250VDC Isolation

WRE/F_P-3WR2

CE

- 2:1 input
- Dual/single outputs
- 3000VDC Isolation
- Efficiency up to 86%

URE/F/H_P-6WR3

CE CB

- 4:1 input
- 3000/6000VDC Isolation
- No-load power consumption as low as 0.12W

URB_S-6WR3/10WR3

CE

- 4:1 input
- Single output
- No-load power consumption as low as 0.12W

URB_ZP-6WR3
URA/B_ZP-10WR3

CE CB

- 4:1 input
- Dual/single outputs
- 1500VDC Isolation

WRA/B_ZP-3WR2

CE

- 2:1 input
- Dual/single outputs
- 3000VDC Isolation
- Remote on/off

URB1D_LMD-10WR3/
15WR3/20WR3

CE CB

- 4:1 input
- Single output
- 2250VDC Isolation

URA/B_LD-20WR3/
30WR3

CE CB

- 4:1 input
- Single output
- 1500VDC Isolation
- Efficiency up to 90%

URB1D_LD-20WR3
URE1D_LD-20WR3
URF1D_LD-40WR3

CE

- 4:1 input
- 2250VDC Isolation

URB_MT-3WR3

CE CB

- 4:1 input
- No-load power consumption as low as 0.1W
- Efficiency up to 84%

URE/F_LP-10WR3
URF_LP-20WR3

CE CB

- 4:1 input
- Single output
- 3000VDC Isolation
- Efficiency up to 88%

VRB_J(M)D/T-6W
URB_J(M)D/T-10W/15W

CE CB

- 4:1 input
- Single output
- Efficiency up to 86%

URB_YMD-6WR3/
10WR3/15WR3/20WR3
URA_YMD-20WR3

CE CB

- 4:1 input
- Dual/single outputs

75 to 200 Watts

URF_QB-75W/100W/150W/200WR3

CE

- 4:1 input
- Efficiency up to 94%
- 2250VDC Isolation

Non-isolated

K78L-500R3/1000R3

CE

- Open frame
- Efficiency up to 95%
- Ultra low no-load power consumption
- Short circuit protection

K78xxM-1000R3

CE

- Efficiency up to 96%
- Low no-load power consumption
- Short circuit protection

K78T-500R3/1000R3
K78_JT-500R3

CE

- Efficiency up to 95%
- Low no-load power consumption
- Short circuit protection

K78-500/1000/2000R3
K78_W-500R3

CE

- Efficiency up to 96%
- Pin-out compatible with LM78XX linear regulators
- Short circuit protection

K12T-6/10/16A(N/P)

CE

- POL power converter
- Single output
- Efficiency up to 94%

Photovoltaic Power Supply



PV10-27C
PV15-29C
PV45-29D
PV60-27D

CE

- 10/15/45/60 Watts
- Dual/triple outputs

PV(05-200)-27B

CE

- 5/10/15/40/120/200 Watts
- 100-1200VDC input
- 4000VAC isolation
- Single output

PV(15-200)29B

CE

- 15/40/200 Watts
- 200-1500VDC input
- 4000VAC isolation
- Single output

DC/DC Converter for IGBT Driver

QA01/02/03/04

CE CB

- ±10% Input
- Ultra low isolation capacitance
- 3000VAC Isolation
- No-load operation allowed

QA01C

CE CB

- ±10% Input
- 3500VAC Isolation
- Designed for SiC Driver

QA152D

CE CB

- ±10% Input
- 3500VAC Isolation
- Designed for SiC Driver

QAW01/02

CE

- 2:1 Input
- 0.24-4.8W
- 3000VDC Isolation
- Output over-voltage Protection

QA051C

CE

- Efficiency up to 79%
- 5200VDC Isolation
- Continuous short circuit protection

QAU242D2G

CE

- 4:1 Input
- Dual outputs
- 3000VDC Isolation
- Efficiency up to 85%

Railway Power Supply



URB1D_YMD-6WR3
URB1D_LMD-10/15/20WR3
URB/URE1D_LD-20WR3
URF1D_LD-40WR3

CE

- 6-40 Watts
- 40-160VDC Input
- Single output
- 2250/3000VDC Isolation

URF1D_QB-50/75WR3
URF1D_QB-100/150/250WR3

CE

- 50/75/100/150/250 Watts
- 43-160VDC Input
- 3000VAC Isolation
- Meet EN50155 standard

Optional Mountings



PCB Mounting



DIN-Rail Mounting



Chassis Mounting

For more information, please visit www.mornsun-power.com



Position:
Regional Field Application Engineer



Location:
Delhi, Mumbai, Hyderabad



Required to have:
Strong knowledge and experience in AC/DC and DC/DC SMPS design, testing, analysis and application.

Mail you CV to: info@mornsun.cn



mornsun website