



FEEDBACK

YOUR SUGGESTIONS

MOTION DETECTOR

The “Motion Detector Security Alarm Using DigiSpark Development Board” DIY project published in July 2018 issue is quite interesting. The same is also available on your website, <https://electronicsforu.com>. Where can I get digi_motion.ino source code mentioned in the project?

Denis Papp

Through email

EFY. Thanks for the feedback! You can download the code from:

<http://efy.efymag.com/admin/issuepdf/Motion%20detector%20for%20security%20alarm.rar>

VIRTUAL TELEPRESENCE

In “Virtual Telepresence Robot Using Raspberry Pi” DIY project published in March 2018 issue, two microcontrollers (Raspberry Pi and Atmega2560) are used. Can one microcontroller or Raspberry Pi alone do the job?

Varsha Vishwa Kiran

Through email

The author Shamin P. Shaji replies:

I had noticed some video transmission delay with all functions using Raspberry Pi. The system-on-chip (SoC) in Raspberry Pi is not powerful enough to handle everything. If the navigation controller using ATmega2560 hangs or does not work properly, you can try programming the entire navigation control remotely through Raspberry Pi.

DESIGN ANDROID APP

Thanks for publishing “Designing Android App For Communication With Bluetooth Module” DIY project in March issue! I have successfully assembled this project and it is working fine. It was possible because of your well-written article and step-by-step instructions.

I would like to know the following:

1. What can I use with ESP32, instead of HC-05?
2. How can I increase the number of

From electronicsforu.com

Electronics Projects

In “Motion Detector Using NE555 Timer” DIY project available on your website <https://electronicsforu.com>, what is the range of PIR sensor used?

Atul Rath

EFY. The range of PIR sensor is around seven metres.

In “Automatic Bike Turn Indicator” DIY project available on your website <https://electronicsforu.com>, why does the author’s prototype have only four capacitors, whereas total capacitors in the circuit are eight?

Josh Schaefer

EFY. The given circuit is correct. In the prototype, some components on the solder side of the PCB are not visible.

The “Fire Extinguishing Robot” DIY

project available on your website <https://electronicsforu.com> is a nice one.

Birudev Battatraya Gadade

EFY. Thanks for the feedback!

In “Real-Time Face Recognition Using Python and OpenCV” DIY project available on your website <https://electronicsforu.com>, is it necessary to use Ubuntu?

Sadu

EFY. No, you can test it on Windows also!

This is regarding “Voice Recorder and Playback System” DIY project available on your website <https://electronicsforu.com>. Can it play the recorded message multiple times?

Kelly Ollos

EFY. Yes!

devices in the circuit?

3. Is it possible to add two or more Bluetooth devices (or a mesh network)?

4. How can I make the circuit work on Wi-Fi instead of Bluetooth, or using both, as in ESP22?

5. How can I make Wi-Fi app in MIT App Inventor? I tried to make the same with ESP32 but Bluetooth of ESP32 is not working.

M.K. Butan

Through email

The author Mahendra Raisinghani replies point by point:

1. You might notice Bluetooth client in this project but not any other module series. It should work with other Bluetooth devices, but I tried it with HC-05 and HC-06 only. HC-05 is based on Bluetooth version 2.0, while ESP32 has Bluetooth version 4.2, so both are different.

2. It is limited to transfer one Bluetooth device at a time. However, you can switch to other Bluetooth devices available in the list you paired with.

One Bluetooth module is enough for getting data, but you can create different buttons on the first page. On clicking the button, a new screen will open. Use the same Bluetooth blocks for each screen so you can have many serial monitors.

3. Answered above in point 2.

4. Add these functionalities to another screen if you want to use both Wi-Fi and Bluetooth. For Wi-Fi, connect your device with access point (AP) and get its IP address—which you will use—from the app. For example, if you want to turn on and turn off an LED, make two buttons: one for high and other for low. Add Web Viewer from user interface, where you will get data (same as serial monitor but for Web data). H is used for high and L for low, as in my program.

Then, add functionality to buttons in blocks. On clicking Turn On button, make Web Viewer access GoToUrl link and add a text box with IP, like <http://192.168.1.13/H>. On clicking Turn Off button, make Web Viewer access GoToUrl link and add a text box with IP, like <http://192.168.1.13/L>.

5. Answered above in point 4.