

NXP i.MX 8 SoCs. The most performant i.MX 8 SoC, i.MX 8QuadMax features 2x Cortex-A72 and 4x Cortex-A53 applica-



tion processor cores and 2x additional Cortex-M4F, which also includes an FPU, microcontroller (MCU) cores. The modern Cortex-A cores support Armv8 64-bit instruction set. The integrated high-performance dual GC7000 3D GPU supports OpenGL 3.0, OpenGL ES 3.1 and Vulkan on up to 4x 1080p or one 4K display. An additional Tensilica HiFi 4 DSP adds flexibility for a variety of applications that can be offloaded from the main cores.

Toradex
www.toradex.com

Power module

RECOM's new power module offers a high power density footprint on a 4.5mm x 4mm x 2mm thermally-enhanced QFN package. RPX-2.5 provides an input range from 4.5V DC to 28V DC, allowing 5V, 12V or 24V supply voltages to be used. Output voltage can be set with two resistors in the range from 1.2V up to 6V. Maximum output current is 2.5A, and output is fully protected against continuous short-circuits, output overcurrent or over-temperature faults. It has an efficiency of up to 91 per cent, and it is thermally-optimised due to its flip-chip technology.

RECOM Asia Pte Ltd
www.recom-power.com

Hall effect base current sensor

WCS1700 current sensor provides an economical solution for both DC and AC current sensing in industrial, commercial and communication systems. It consists of a precise, low-temperature drift linear hall sensor IC with temperature compensation circuit. Other features are:



- High sensitivity: 33mV/A
- Output voltage proportional to AC and DC current
- Wide operating voltage range: 3.0 ~ 12V
- Low operating current: 3mA
- Diameter 9.0mm conductor through hole
- Isolation voltage: 4000V
- Bandwidth: 23kHz

SOURCEWELL
www.sourcewell.in

Audio ICs

To help Bluetooth speaker and headphone manufacturers maintain product differentiation in the competitive wireless audio market, Microchip Technology has released the next generation of its Bluetooth 5.0-qualified dual-mode audio IC and fully certified module. Measuring just 5.5mm x 5.5mm, the low-power IS2083BM IC is ideal for small form factor designs and gives developers more space to use larger batteries in end-products. Both IS2083BM IC and BM83 module enable customers to reduce bill of materials (BOM) with highly integrated features, including:

- Embedded mode
- Integrated power amplifier
- Large flash memory
- Support for Sony's LDAC audio codec technology

Microchip Technology Inc.
www.microchip.com

DC-DC converters

Aedon Russia's MDN series of step-down isolated military-grade SIP pack-



age DC-DC converters provide power capacity from 2W up to 10W with high efficiency to operate within operating temperature range of -60°C to +105°C. These are available in standard metal and plastic SIP-8 cases, as well as a

case-less design version with compound potting. Converters of MDN series differ from most of their analogue ones by a wide range of operating temperatures and higher efficiency.

Rebutor Electronics Pvt Ltd
www.rebutor.com

TEST & MEASUREMENT

Ultrasonic thickness gauge

Metrix+ digital ultrasonic thickness gauge UTM 5A+ features a user-friendly menu operation for selecting the material to be measured, with pre-set sound velocities, user selectable resolution, mm/inch unit for measured values, and many other functions like alarm limits, quiet operation and custom sound velocity measurement. It has memory storage and recall function with integrated statistics of maximum, minimum and average of measured values and material with its sound velocity also stored. With integrated calibration function, the meter can be calibrated easily in case of drifting of values of improper measurement state.

minoo Impex
www.metrixinstrument.com



Network analyser

Anritsu has introduced ME7848A optoelectronic network analyser (ONA) system, a flexible solution integrating VectorStar vector network analyser (VNA) with an O/E calibration detector and E/O converters that conducts cost-effective E/O, O/E and O/O measurements on optical devices operating at 850nm, 1310nm and 1550nm. Incorporating a modular approach, ME7848A provides engineers with an unprecedented level of flexibility and the ability to customise the system with their own devices to meet specific test

