

requirements, for significant time and cost benefits.

Anritsu India Pvt Ltd
www.anritsu.com

Nodal impedance analyser

Qmax's QT-Hi1 is a nodal impedance analyser that uses V-I trace technique of learn and compare of nodal impedances, which are represented as V-I Curves. Its innovative Best Curve fit algorithm is for automatic selection of the best-fit value of voltage, source impedance and frequency of the stimulus waveform.



Compact size of the unit with rechargeable battery makes it the ideal companion for on-field operations. It can store up to four waveforms and also offers dual compare mode for interactive quick checks.

QMax
www.qmaxtest.com

Interface wizard

Pico Technology has announced Pico VNA Interface Wizard, which adds significant functionality and value to the company's low-cost, high-performance vector network analyser (VNA). Pico VNA Interface Wizard links the highly affordable VNA to NI AWR Design Environment. The wizard supports the entire design cycle with import of real-world component, system or sub-system measurements from PicoVNA in a single-click transfer.

Pico Technology
www.picotech.com

Test computing platform

National Instruments (NI) has announced a solution to test the computing platform for autonomous vehicles. NI's solution for testing the complex computing platform consists of modular hardware with a configurable set of I/O that includes power measurements, thermal performance, automotive networks, sensor interfaces and PCB electrical measurements. Inherent flexibility in the modular design of NI's

solution means that automotive test teams can add measurement capabilities to the test system without buying a new system or starting from scratch. Footprint of the PXI-based system is also much smaller than that of a system composed of benchtop instruments. The holistic platform approach simplifies system complexity and reduces the burden on test teams to integrate disparate pieces of test equipment.

National Instruments
www.ni.com

MISCELLANEOUS

Access control IP panel

Matrix COSEC ARC DC200 is a standalone access control IP panel based



on IP-to-door concept, eliminating the need for age-old individual cable-laying requirements between access panel to a reader or lock for access control applications. It supports two Matrix RFID or fingerprint readers on RS-485 or third-party readers on Wiegand interface for entry or exit. SSL-based secure communication between controller and server makes it ideal for critical or simple access control applications for any organisation.

Matrix Comsec
www.matrixcomsec.com

NFC programming technology

For fast and cost-effective implementation of NFC programming for LED drivers, Infineon Technologies has developed NFC-PWM series NLM0011 and NLM0010. NFC programming is an emerging technology designed to replace the labour-intensive plug-in resistor current setting method via contactless NFC interface. Besides improving the operational efficiency by enabling automatic programming in the manufacturing line, it creates significant flexibility

in the value chain. With this it reduces LED driver variants, simplifies selection of LED modules and allows end-of-line configuration.

Infineon Technologies AG
www.infineon.com

Development kit

MSP430G2553 LaunchPad development kit is an inexpensive and easy-to-use evaluation module (EVM) for

MSP430G2xx entry-level series of microcontrollers (MCUs). It contains everything needed to start developing on the ultra-low-power MSP430 MCU platform, including an onboard debug probe for programming, debugging and energy measurements. The board also features a push button and three LEDs for creating a simple user interface.

Rajguru Electronics (I) Pvt Ltd
www.rajguruelectronics.com

Software IP probe

ipoque GmbH, a Rohde & Schwarz company, has announced its new software IP probe, R&S Net Sensor OEM. Designed with unique flexibility, scalability and versatility, R&S Net Sensor OEM meets the demands of network analytics and cybersecurity vendors, as well as those of system integrators, regardless of setup and use-case.

ipoque GmbH, (a Rohde & Schwarz company)
www.ipoque.com, www.rohde-schwarz.com

Ultrasonic sensor disks

TDK has released a new series of ceramic-based EPCOS ultrasonic sensor disks, comprising two standard types. B59050Z0206A030 sensor disk has a diameter of 5.0mm and a thickness of 1.02mm. With a serial resonance frequency of 2000kHz it features thickness oscillation mode (axial), making it suitable for use in liquid media.

B59070Z0285D12 has a diameter of 7.0mm and a thickness of 0.195mm. It offers a radial mode of oscillation at 285kHz, and is suitable for operation in air.

TDK India Pvt Ltd
https://in.tdk-electronics.tdk.com/en-in