



COMPONENTS

Fine ranging chipset

NXP Semiconductors has announced its secure fine ranging chipset, SR100T, designed to bring remarkably precise positioning performance tailored for next-generation UWB-enabled mobile devices. With SR100T, mobile devices will be able to communicate with connected doors, points of entry and cars to open them. Lights, audio speakers and any other connected device with UWB sensing capability will be able to follow users from one room to another, and smart connected technology will intuitively be embedded in people's lives.

NXP Semiconductors N.V.

www.nxp.com

Output driver

Analog Devices has announced a simple power solution that maximises efficiency and minimises electromagnetic (EM) emissions of motion systems as customers migrate to higher density automation. ADuM4122, an isolated, dual-drive strength output driver that uses iCoupler technology, empowers designers to harness the benefits of higher efficiency power switch technologies. ADuM4122 efficiently toggles between two slew rates controlled by a digital signal. Smaller than existing discrete or complex integrated solutions that have twenty or more pins, ADuM4122 features only eight pins and works in a variety of operating conditions.

Analog Devices

www.analog.com

DC-DC converter

Minmax Technology has released MJWI30 series, isolated 2.54cm x 2.54cm (1-inch x 1-inch) DC-DC converter modules that enable designers of applications with a maximum load rating up to 30W to greatly reduce their power system's size and weight. Operating over wide 4:1

input voltage ranges of 9V DC to 36V DC or 18V DC to 75V DC, MJWI30 is available in versions with a fixed single output voltage of 3.3V, 5V, 12V, 15V or 24V DC, or a dual output of $\pm 12V$ or $\pm 15V$ DC. Output voltage can be trimmed to ± 10 per cent of its nominal value.

Minmax Technology Co. Ltd

www.minmax.com

Converter

RAC03-K modules deliver an output power of 3W from -40°C to 60°C , and 2W up to 80°C . Despite high power density and small footprint, RAC03-K series is a complete solution supporting Ecodesign Lot 6 standby mode operation for worldwide applications in automation, Industry 4.0, Internet of Things (IoT), household and home automation. An input voltage range from 85V AC to 264V AC, and international safety certifications for industrial, domestic, ITE and household applications make these extremely versatile power modules.

RECOM Asia Pte Ltd

www.recom-power.com

DC/DC input filter module

This filter module is created to accommodate the need to meet railway standards of EN55015 standard, and Fire and Smoke EN45545-2. It saves the trouble of meeting necessary requirements for railway applications. The module is suitable for any of Cincon's railway DC-DC converters that have input current less than 10A, and input voltage lower than 200V DC. Also, it offers an isolation voltage of 3000V DC

Elcomsys

www.elcomsys.sg



DC/AC inverters

ODX-6000 is a series of three-phase sinusoidal DC/AC inverters of up to 6000W that offer high density, efficiency up to 93 per cent and uses SiC technology. All models are available in railway version, complying with EN50155 and EN45545-2 standards. Features include adjustable output frequency, output voltage, high input-output isolation 3000Vrms, remote on/off opto-coupled, alarm by isolated relay contacts, rotation inversion, remote control via RS232, CAN BUS and parallelable output.



Rebutor Electronics Pvt Ltd

www.rebutor.com

Microcontroller

Holtek has released its new charger application specific microcontroller (MCU), HT45F5Q-3. This device integrates two groups of OPAs and a 12-bit/14-bit D/A converter to allow the charger to control multiple groups of constant currents and constant voltages. When used together with HT45F5Q-x series charger volume production calibration platform, it allows calibration data to be stored in the device's internal emulated EEPROM. Using this method, in addition to allowing more rapid and efficient production, it also permits voltage and current accuracy of up to ± 1 per cent.

Holtek Semiconductor India Pvt Ltd

www.holtek.com

High-voltage converter

STMicroelectronics VIPer26K high-voltage converter integrates a 1050V avalanche-rugged N-channel power MOSFET that enables offline power supplies to combine a wide input-voltage range with the advantages of a simplified design. The extremely high voltage rating of VIPer26K MOSFET eliminates the need for conventional stacked FETs and associated passive

