

components to achieve similar voltage capability, and smaller external snubber components can be adopted. Drain current-limit protection is built-in, and the MOSFET includes a senseFET connection for over-temperature protection.

STMicroelectronics India

www.st.com

TEST & MEASUREMENT

Radio communication test station

Anritsu has announced radio communication test station MT8000A with upgraded 5G Protocol Test functions that support 3GPP TS 38.521-4 B.1/B.2 V15.0.0-compliant 5G NR channel (TDL) model tests using NR Fading software implementing built-in baseband fading tests. MT8000A is an all-in-one test platform



for RF, protocol and beam tests, as well as for beam-forming evaluations. In

addition to supporting functions for simulating base-station NSA and SA modes required for development of 5G chipsets and terminals, it also supports the latest technologies, such as 4x4 MIMO for increasing data transmission speeds in the sub-6GHz band as well as 8CC for implementing wideband mmWave.

Anritsu India Pvt Ltd

www.anritsu.com

Clamp meter

CM94 clamp meter is designed to tackle high-current measurements in demanding utility and industrial job sites. Its oversized, 55mm jaw can securely clamp around conductor wires and busbars for accurate readings up to 2000A AC and DC. Designed with CAT IV-1000 V safety rating, CM94 is ready to work on relays, distribution panels and switch-gear as well as service conductors, feeders, and production power lines. VFD mode allows users to tackle noisy signal environments to ensure correct measurements when working on large motors and motor controls.

FLIR Systems India Pvt Ltd

www.flir.in



Semiconductor test system

National Instruments (NI) has announced semiconductor test system (STS) software enhancements that deliver significant improvements to the programming and debugging experience, test execution speed, parallel test efficiency and overall equipment efficiency for NI semiconductor test system. STS software 2019 offers users who do not have access to the tester, an improved offline experience for developing test programs. Further improvements include a simplified driver experience for programming duplicate instruments and simplified digital scan support.

National Instruments

www.ni.com

Digital storage oscilloscope

SIGLENT's SDS5000X series digital storage oscilloscopes are available in bandwidths of 1GHz, 500MHz and 350MHz, have a maximum sample rate of 5GSa/s, maximum record length of 250Mpts, and



display up to four analogue channels and sixteen digital channels with mixed-signal analysis ability.

SDS5000X series employs Siglent's SPO technology with a maximum waveform capture rate of up to 110,000wfm/s in normal mode and up to 480,000wfm/s in sequence mode, 256-level intensity grading display function plus a colour temperature display mode.

Siglent Technologies Co. Ltd

www.siglent.com/ens/

LEDs

LED driver

ROHM has announced its latest LED driver IC, BD81A76EFV-M, optimised for LCD backlight in instrument cluster, information displays and car navigation. Unlike conventional drivers with four channels that support LCDs up to 20.3cm (8 inches), this IC provides six channels of output (with 120mA per channel) that can support LCD panels of up to 25.4cm (10-inch) to 30.5cm (12-inch) class. Original buck-boost control

ensures compatibility with both small and large LCDs using a single driver.

ROHM Semiconductor India Pvt Ltd

www.rohm.com



LED driver ICs

Power Integrations has announced high-power-density members of its LYTSwitch-6 family of safety-isolated LED-driver ICs for smart-lighting applications. The new ICs with PowiGaN technology enable designs that deliver up to 110W with 94 per cent conversion efficiency using a simple, flexible flyback topology.

High efficiency of the ICs eliminates the need for heatsinks, greatly reducing ballast size, weight and cooling airflow requirements. The 750V PowiGaN primary switches provide very low R_{DS(ON)} and reduced switching losses.

Power Integrations

www.power.com



MISCELLANEOUS

Face-recognition system

Matrix COSEC face recognition is based on innovative, deep learning technology, which evolves as per regular user interaction in different conditions. It ensures contactless authentication and identifies user's face in one second. It can read beyond the surface of the skin and identify real skin within a fraction of a second. Key features are:

- Works with different usage scenarios
- Higher accuracy and speed
- Auto-push technology
- Ready device API
- Encrypted communication
- Multiple deployment modes
- Future-ready connectivity
- Multiple credentials
- IK08 and IP65/66 design

Matrix Comsec

www.matrixcomsec.com

Automation ecosystem

PLCnext technology is a unique, open ecosystem for modern automation that can meet all challenges of the Internet of Things (IoT) world. The combination