

of open control platform with PLCnext control hardware devices, modular engineering software—PLCnext Engineer—for configuration, commissioning and programming in accordance with IEC 61131-3, and systemic cloud integration enables simple adaptation to changing demands and efficient utilisation of existing and future software services.

Phoenix Contact (India) Pvt Ltd
www.phoenixcontact.co.in

Compact colour display

Electronic Assembly has designed the 5.08cm (2-inch) TFT020-23 as a full-colour alternative to monochrome graphic displays, which are widely used in handheld devices. Despite its compact size of



only 36mm x 52mm, it features a very fine resolution of 240 x 320 pixels. With

a brightness of 1000 cd/m² it delivers brilliant images in the office, production or operating room, even in bright sunlight. Thanks to IPS technology, the crisp, sharp contrast is preserved over a wide viewing angle of 160°, and colours remain unchanged, even at the most oblique viewing angle.

Electronic Assembly GmbH
www lcd-module.com

Thermal ticket printer

KP628E is a 58mm kiosk/ticket thermal printer module. It has auto paper loading with full/partial cutter. It supports no paper and paper near end detection. It also supports 90°/180° paper loading. Other features are:

- Interface: RS232/TTL + USB
- Power: 5V DC - 9V DC/12V DC, 2A
- Resolution: 203dpi
- Printing speed: 90mm/s (maximum)
- Paper diameter: 80mm (maximum)
- Reliability: TPH (50km0, cutter (on million cuts)
- Compatible with ESC/POS command set

Sourcewell
www.sourcewell.in



Wi-Fi connectivity cloud kit

Renesas Electronics has announced Renesas RX65N cloud kit featuring onboard Wi-Fi, environmental, light and



inertial sensors, and support for Amazon FreeRTOS connected to Amazon Web Services (AWS). The kit gives embedded designers a fast start and secure connection to AWS. Using Renesas' e2 studio integrated development environment (IDE), IoT applications are easily created by configuring Amazon FreeRTOS, all necessary drivers, and network stack and component libraries.

Renesas Electronics Corp.
www.renesas.com

Biometric attendance device

Mantra's biometric time attendance and access control device MFSTAB II addresses both access control and time attendance system requirement of an organisation. It has advanced biometric fingerprint scanner, which is a PIV/STQC-certified FAP10 scratch-free biometric fingerprint sensor. The device comes with a capacitive scratch resistant touchscreen. It utilises the latest biometric technology to authenticate and identify users with the help of their unique fingerprint impressions.

Mantra
www.mantratec.com



Power modules

Infineon Technologies has launched two new EasyPACK modules of 1200V family. Both, Easy 1B and Easy 2B, integrate CoolSiC MOSFETs aiming not only at this market but also at UPS applications. Coming in two different topologies, the power modules enable engineers to increase their systems' efficiency for reduced cooling effort. In addition, higher frequency operation is possible. Integrated in an Easy 1B housing, the four-pack topology (F4-23MR12W1M1_B11) perfectly serves the DC/DC stage of the charging station.

Easy 2B (F3L15MR12W2M1_B69) holds a three-level configuration that is well-suited for Vienna Rectifier usually implemented in this application for PFC stage.

Infineon Technologies India Pvt Ltd
www.infineon.com

Battery protector

Designers concerned about battery safety now have access to an advanced battery protector with integrated fuel gauges from Maxim Integrated Products. The new one-cell, pack-side ICs in this portfolio are MAX17301 and MAX17311, which offer the most configurable settings for battery safety in the industry and uniquely allow fine tuning of voltage and current thresholds based on various temperature zones.

These ICs also offer a first-of-its-kind secondary protection scheme in case primary protection fails. All ICs in the family are equipped with Maxim's patented ModelGauge m5 EZ algorithm.

Maxim Integrated Products Inc.
www.maximintegrated.com

Power supplies

R&S NGL200 and R&S NGM200 series switch from a few µA in sleep mode to several A in active mode, and benefit from exceptionally fast load recovery time of less than 30µs. The two-quadrant architecture provides both source and sink functions, to simulate charging and discharging of batteries as well as to operate as an electronic load. The large capacitive touchscreen and simple operating concept set new standards for power supplies.

Rohde & Schwarz GmbH & Co. KG
www.rohde-schwarz.com

Flight controller

Pixhawk 4 is the latest update to the family of Pixhawk flight controllers. It is designed and developed in collaboration with Holybro and PX4 team, is optimised to run the full drone code stack and comes preinstalled with the latest PX4 firmware (v1.7). Pixhawk 4 is equipped with sensors having higher temperature stability, integrated vibrations isolation, increased ease-of-use, and extra ports for better integration and expansion.

Macfos Pvt Ltd
www.robust.in