

SLS delivers the most powerful Evaluation Board for IoT projects

NEBULAE
DESIGN TO CONNECT



EVB NLN 100c is a convenient system designed to enable users to develop their specific use cases and make a complete working prototype. It contains components that can be used to create a ZigBee or 6LowPAN node based on Nebulae framework.

It demonstrates the ability to utilize one of the multiple energy sources to power a wireless sensor node containing the RF SoC module, multiple IOs, LEDs, Push Button, etc for specific needs.

FEATURES

- NebuLink NLN100c Module interconnection
- GPIO interface headers
- Buffer circuit for analog input
- U.FL connector for external antenna
- Single relay (DPDT) output with capacity of 230VAC, 180mA
- User-input button
- 1 green and 1 red LED for debug purposes
- Powering options:
 - 2 AA batteries
 - External 0-6V DC supply
 - USB Micro connector

SPECIFICATIONS

Operating Temperature	-10°C to +50°C
Operating Humidity	Up to 85% non-condensing
Dimensions	79mm x 45mm x 10mm

*Requires Gateway to complete the eco-system

Contact us at **+91 2692 232501(ext. 47)** or Write to us at **sales@nebulae.io**



System Level Solutions

UK • INDIA • USA
www.slscorp.com



Scan QR Code or visit
www.nebulae.io