

NEW PRODUCTS

MAKE IN INDIA

TEST & MEASUREMENT

In-building testing solution

For in-building testing requirements, Transcom has introduced a new testing solution that takes only five seconds to finish operator frequency



power measurement and data collection within the range of 700-2700MHz and automatically outputs the result report. With IB-TX sweep signal source and IB-RX sweep signal receiver, all frequency point testing results can be automatically output in one test. The testing solution has a wide power testing range of -120dBm to +20dBm.

Transcom Instruments
www.transcomwireless.com

Digital multimeter

Kusam-Meco has introduced a 3 1/2-digit, 1999-count digital multimeter with terminal blocking system. The multi-



meter, Model KM-6030, has a large (28mm) LCD. To avoid improper connection operation, the current terminal sockets are blocked by a mechanical protection device

when the range switches in V, Ω or Hz function. The meter has 14 functions and 33 ranges. It can measure AC/DC voltage, AC/DC current, resistance, capacitance, frequency and temperature, and perform transistor hFE and diode testing. It also has a data hold function.

Kusam-Meco
www.kusamelectrical.com

Baseband vector signal transceiver

National Instruments has introduced baseband model of its second-generation vector signal transceiver. The new transceiver has 12 times the bandwidth, a 50 per cent smaller footprint



and a larger user-programmable FPGA. The PXIe-5820 module has 1GHz of complex I/Q bandwidth and is designed to address the most challenging RF front-end module and transceiver test applications, such as envelope tracking, digital pre-distortion and 5G test. It combines a wideband I/Q digitiser, wideband I/Q arbitrary waveform generator and high-performance user-programmable FPGA into a single two-slot PXI Express module.

National Instruments
www.ni.com/vst/

Signal quality analyser

Anritsu has introduced a versatile signal quality analyser, MP1900A BERT, that can measure next-generation PCI Express Gen 4 and Gen 5 buses, as well as the latest 400GbE/200GbE Ethernet networks. With comprehensive interface support, the MP1900A is



an all-in-one solution that accurately measures next-generation high-speed electronic and optical devices, and optical transceivers used in high-end servers, communications equipment and optical transceivers/modules, including those for M2M and IoT applications. It supports simultaneous multi-channel measurements, PAM4 BER tests and PCI Express link negotiation.

Anritsu India
www.anritsu.com

Insulation tester/true RMS multimeter

FLIR Systems' MG320 portable 20G Ω /1000V insulation tester

combines a true RMS multimeter. It includes PI/DAR modes, programmable timer and a comparator for custom test configurations and quick results. Multimeter functions include AC/DC voltage and resistance meas-

