


urement, and continuity test. The device can manually store/recall up to 99 readings. It has a large backlit 6000-count LCD display with analogue bargraph, and meets CAT IV-600V safety standard.

FLIR Systems India
www.extech.com

COMPONENTS

USB Type-C port-controller ICs

STMicroelectronics has introduced two new USB Type-C-certified port-controller ICs with built-in protection, which help designers implement interfaces cost-effectively to support their required blend of USB features. These can include power negotiation, managed active cables and support for guest protocols.



The new controller ICs simplify choices for designers, with one device dedicated to controlling downstream-facing ports, while the other can handle either downstream-facing, upstream-facing or dual-role use. Both ICs support Type-C cable-attachment and connector-orientation detection and can operate over a wide supply range of 3V to 22V with no external voltage regulator.

STMicroelectronics
www.st.com

Wifi eSwitch

The Wifi eSwitch from ARTech




an Internet of Things (IoT)-tested product. It serves as a low-cost home automation product without making any changes in pre-

sent infrastructure of the site. It lets users operate any AC appliance like fans, lights and coolers from any corner of their house effortlessly. The device is easy to install and consume less than 0.6mW per hour of operation.

ARTech
www.artechlabs.in

SMD crystals

Rajguru Electronics has introduced RoHS-compliant SMD crystals from CREC. Typical features of these crystals include 2.5x2.0x0.45mm³ ultra-thin ceramic package, 8mm wide tape and reel package for automatic assembly, and tight tolerance of 10ppm. These find use in Bluetooth, mobile phones, wireless LAN, office automation, and audio-video.



Rajguru Electronics
www.rajguruelectronics.com

Thyristors

Littelfuse, Inc. has introduced a series of 40A standard high-temperature silicon-controlled rectifier (SCR) thyristors that are ideal for use as switches for rectifier and phase control applications such as voltage regulator, heating and motor speed controls.

The new SJxx40x series thyristors can handle 600V, 40A_{avg} and junction temperatures up to 150°C. These are designed to prevent the overheating and thermal runaway problems SCRs experience due to an application's limited cooling capability or occasional overload situation. Also, these trigger with just a few milliamperes of current at less than 1.5V potential.



Typical applications are in a variety of end uses including AC solid-state switches, indu-

trial power tools, exercise equipment, white goods and commercial appliances.

Littelfuse, Inc.
www.littelfuse.com

RF Wi-Fi module

Amp'ed RF Wireless Technology, a provider of advanced IoT wireless modules, has announced the availability of its WF61 module, which is designed for wireless streaming of video supporting up to HD 4k imaging. The WF61 supports both 2.4GHz and 5GHz Wi-Fi bands, bringing together the speed and throughput of dual-band Wi-Fi, and enabling clear high-resolution video. The 5GHz band can handle the greater bandwidth needed for HD 4k imaging. Amp'ed RF provides the Linux kernel to ensure fast development of WF61 applications.

Amp'ed RF Wireless Technology
www.Ampedrftech.com

DC-DC converter modules

Artesyn Embedded Technologies has announced three new series of 50V DC-DC converter modules. These modules support the rapidly growing number of



high-power wireless base station and remote radio head deployments using GaN and high-voltage LDMOS technology for increased power density and higher efficiency.

The AVE450 series offers greater than 95 per cent typical efficiency and up to 10-amp output current. The ADH700 and AVE500 series offer greater than 94.8 per cent typical efficiency and up to 14-amp output current.

Artesyn Embedded Technologies
www.artesyn.com