

Miniature SMD Converter

**RTC2 series: Regulated 2W
with Wide Input Range**

- No minimum load
- SMD package
- 2:1 regulated input
- 3kVDC/1sec isolation
- Superior capacitive load capability
- Ambient temperature range:
from -40°C to +100°C
- MTBF: up to 2 million hrs
- IEC/EN 62368-1 certified
- Ideal for industrial, test & measurement,
process automation and battery-powered
applications



RECOM
WE POWER YOUR PRODUCTS
www.recom-power.com

High Performance & Reliable

Wireless Solutions

Partner For Your Business



GSM Modem : SIM800C

- Voltage input: 5V
- Powered using Micro USB port
- Serial RS232 Interface
- Antenna connector with SMA and UFL option
- Dimension : 50mm x 75 mm

LTE Modem : SIM7600

- Quad-Band TDD-LTE B38/B39/B40/B41
- Tri-Band FDD-LTE B1/B3/B8
- Dual-Band TD-SCDMA B34/B39
- Dual-Band WCDMA/HSDPA/HSPA+ B1/B8
- GSM/GPRS/EDGE 900/1800 MHz
- Control Via AT Commands
- Supply voltage range: 5V (USB)
- Operation temperature: -40°C to +85°C
- Dimension: 65x38 mm
- GNSS gps One Gen 8B; standalone; assisted XTRA



**Starting from
Rs. 1100/- onwards**

AN Wireless Solutions

67, G.K. Arcade, 4th Floor, Bull Temple Road, Basavanagudi
Bangalore - 560004, **Telephone** : 9342825771
Email: anwirelessolutions@gmail.com

IT'S TIME TO PROMOTE DESIGN IN INDIA

<http://designindia.electronicshobby.com>



Design IN India

Section launched on Electronicshobby.com to showcase design houses and innovators of India who are creating innovative electronic hardware products. If your firm has also launched or designed an innovative product for OEMs, share your details with us at editsec@efy.in.

AN
EFY GROUP
INTELLIGENCE