

Spring Contact / Antenna Contact / Grounding Contact / Shield Finger



Surface Mount Spring Contacts available in 30 different types, ranging from 1.23mm to 7.25mm free height (0.89mm to 6.35mm working height).

A comprehensive range of single spring contacts, suitable for shielding, grounding, mobile phone antenna and other general electrical connection applications. All contacts are Surface Mount, supplied in Tape and Reel packaging for automated assembly placement.

- NEW! Development Kit DEV-001 with 16 different contacts and free refills.
- 30 different designs, ranging from 1.23mm to 7.25mm vertical free heights.
- Option of horizontal spring contacts for 90 degree connection
- Protected tip options to prevent hooking.
- Positive stop options, to prevent over-stressed contacts.
- Mounted in a row, the contacts can provide an excellent RFI shielding connection for metal doors or other cabinet enclosures.
- The contact design ensures positive contact with the mating surface, and is tolerant to both wiping and sliding action.

The Spring Contact Development Kit is the ideal prototyping kit for customers using **SMT Spring Contacts**. Containing 16 different contacts in strips of Tape and Reel, the kit is an easy reference library for Harwin's product range. Electronic Design Engineers at OEMs and Design Houses can now immediately try out one or more of the contacts by keeping this kit on hand, instead of waiting for the delivery of samples contacts.