

NEW PRODUCTS

MAKE IN INDIA

TEST & MEASUREMENT

Digital multimeter

The new Testo 760 digital multimeter family comprises three models for all electrical measuring tasks. Testo 760-1 is for daily measuring tasks. Testo



760-2 has a larger current measurement range, trms measurement and a low-pass filter for VFD output voltage measurements accurately.

Testo 760-3 has a voltage range of up to 1000V, along with higher measuring ranges for frequency and capacitance.

Testo India Pvt Ltd
www.testo.in

Power and harmonics analyser

Meco's latest, model 5850, is ideal for carrying out vigilance checks, surveys and audits. It has a large dot-matrix LCD display to monitor energy, active power, apparent and reactive power, power factor, energy, true-rms value, AC current, and average and maximum demand with programmable time interval and CTR and PTR.



Meco Instruments Pnt Ltd
www.mecoinst.com

Multichannel power probe

The new R&S RT-ZVC multichannel power probe, in combination with R&S CMW radio communication tester,



monitors the power consumption of chipsets, radio modules and mobile devices. It can correlate

battery consumption data with RF signaling events. And it accomplishes this with a measurement resolution of 18 bits, making measurements in the nano-ampere range possible.

Rohde & Schwarz India Pvt Ltd
www.rohde-schwarz.com

Oscilloscopes

Keysight has announced ultra-low-cost InfiniVision 1000 X-Series oscilloscopes that have 50MHz to 100MHz models featuring Keysight's MegaZoom IV custom ASIC technology, which enables 50,000 waveforms per second update rate.



This makes it easier to see random and infrequent anomalies. The scopes have sampling rate of up to 2GSa/s and come with two probes. These use segmented memory capability to maximise memory depth while helping the scope test faster.

Keysight Technologies
www.keysight.com

Thermal imaging cameras

FLIR Systems has announced Exx-Series advanced thermal imaging cameras for electrical, mechanical and building applications: FLIR E75, E85 and E95. The Wi-Fi-enabled Exx-Series features intelligent interchangeable lenses, laser-assisted auto-focus modes and area measurement functionality, improvements to FLIR's patented MSX imaging technology and a larger touchscreen. These features, combined with increased sensitivity and increased native resolution, will help professionals identify hot spots or building deficiencies before potential problems become expensive repairs.



FLIR Systems India Pvt Ltd
www.flir.in

COMPONENTS

Microcontrollers

The new ATtiny1617 series of microcontrollers feature core independent peripherals, which help increase system throughput while lowering

overall power consumption. These offer 16kB flash, 256B EEPROM and 2kB RAM in 14-, 20- and 24-pin packages.



Microchip Technology Inc.
www.microchip.com

DC/DC converter

RECOM's new converters REC3A, REC5A and REC6A have a built-in EMC filter to meet EN55022, class A. Class B can be achieved with a small capacitor. The compact DIP24 modules provide regulated 5V DC output and can be operated on zero per cent minimum load. The converters can be operated in a wide temperature range of -40°C to +100°C.



RECOM Power
www.recom-power.com

TVS diode arrays

Littelfuse has introduced a series of three unidirectional TVS diode arrays in 01005 flip-chip packages. These can withstand multiple ESD events without wear-out or degradation.



Their low nominal capacitance (0.35pF) make these ideal for interfaces running at high data rates approaching 5GHz clock speeds.

Littelfuse Inc.
www.littelfuse.com

Digital-to-analogue converter

TI's new digital-to-analogue converter combines precision performance with simpler power-supply design. The 16-bit DAC8775 operates from a single, wide 12V to 36V power rail, leveraging an integrated buck/boost converter to generate all required internal power supplies to save time, cost and significant board space.



Texas Instruments Inc.
www.ti.com