

NEW PRODUCTS

MAKE IN INDIA

TEST & MEASUREMENT

Multifunction meter

MECO-G has introduced R-27A multifunction network instrument that can measure more than 50 electrical



parameters in electrical circuits. Readings are displayed on a 7-segment bright red LED display in five

rows. The meter has 2-channel electrical energy pulse outputs, 4-channel switching value inputs and RS485 communication output with Modbus protocol. Four-channel switching value outputs or 4-channel transmitting outputs are also available.

The meter operates off 85-264V AC/DC auxiliary supply, and comes in 96x96mm² size. It is ideal for panel builders and power monitoring systems.

Goliya Instruments
www.goliyainstruments.com

Function/arbitrary waveform generators

Siglent's SDG6000X series dual-channel pulse/arbitrary waveform generators feature up to 500MHz bandwidth, a maximum sample rate of 2.4GSa/s and 16-bit vertical resolution. These also include proprietary TrueArb and EasyPulse technologies that help to solve the weaknesses



inherent in traditional DDS generators when generating arbitrary, square and pulse waveforms. In addition, the SDG6000X is a multi-function device that can generate noise, IQ signals and PRBS patterns.

Siglent Technologies
www.siglent.com/ens

PXI chassis for test systems

National Instruments (NI) claims its PXIe-1095 to be the industry's first PXI chassis with 58W of dedicated power and cooling per slot. This represents a 50 per cent increase in power and cooling per slot compared to previously released NI PXI Express chassis.



The new chassis also emits significantly less fan noise in its 38W cooling profile mode, delivering a 13dB improvement. In addition, it offers two hot-swappable, redundant 1200W power supplies for high-availability applications.

National Instruments
www.ni.com

WLAN device test software

Anritsu's WLAN security function MX886200A-020 software for MT8862A supports evaluations of WLAN devices for the rapidly growing Internet of Things (IoT) market. Wireless connectivity test set MT8862A uses 'network mode' measurement function to execute tests while the WLAN device is actually operating.



Adding this new security function supports evaluation while the built-in security of the WLAN device is 'on.'

Anritsu India
Anritsu.com


COMPONENTS

SMD fuse

SCHURTER's USN1206 temperature-sensitive SMD fuse is suitable for both overcurrent protection

and protection against excessive ambient temperatures. It

requires a current flow to blow, thus providing protection against overcurrent just as well as any conventional fuse. In addition, it protects power semiconductors in automotive applications against overtemperature. The fuse has a current-time characteristic that shifts as a function of the ambient temperature. The fuse is reflowable at 245°C according to IEC 60068-2-58.



SCHURTER Electronics (India)
www.SCHURTER.co.in

Transceivers

Industrial designers can now achieve two times faster data rates and extend cable length by up to 50 per cent with new RS-485 transceivers from Maxim Integrated Products. The MAX22500E/

