


MAX22501E (half-duplex) and MAX22502E (full-duplex) ESD-protected RS-485/RS-422 transceivers extend the reach of communication up to 100Mbps over 50m. A large receiver hysteresis (250mV) provides superior robustness to EFT. The transceivers operate over -40°C to +125°C temperature range.

Maxim Integrated Products
www.maximintegrated.com

Switching regulator

ROHM has introduced a new power supply chip for electric vehicles. The BD9V100MUF-C is a 2MHz switching



regulator with built-in MOSFET, useful for 48V automotive systems such as mild hybrid vehicles. It uses an ultra-fast switching technology called Nano Pulse Control to achieve a very high step-down ratio (60V:2.5V) at a constant frequency of 2MHz.

ROHM Semiconductor India
www.rohm.com/web/in

Wireless charging chip

STMicroelectronics has introduced a new wireless charging chip that enables smartphones and tablets to be charged up to three times faster by



increasing the maximum charging power from 5W to 15W.

According to the company, the STWBC-EP is the world's first charging controller to support the latest industry standard (Qi Extended Power) for faster charging of smartphones and tablets. The chip consumes just 16mW in standby mode and wirelessly transfers more

than 80 per cent of the total input power.

STMicroelectronics
www.st.com

Voltage regulator

Infineon Technologies AG has launched the IRPS5401, a five-output point-of-load (POL) digital voltage regulator for FPGAs, ASICs and other multi-rail power systems. The IRPS5401 replaces multiple regulators with a single device in a compact 7x7mm² 56-pin QFN package. It is a perfect fit for current and future applications in high-density ASICs and FPGAs. Additional applications include CPU multi-rail systems, embedded computing systems, and communication and storage systems.



Infineon Technologies AG
www.infineon.com/irps5401

AC capacitors

CSDiN's MKP and MPB series of film capacitors are suitable for AC applications. These are available for rated voltages of 250Vrms, 275Vrms, 330Vrms and 440Vrms, and cover capacitance range of 0.01 to 70 micro-farads. The capacitors find application in energy meters, motor controls, power equipment and welding equipment.

Shenzhen CSD Electronics
csdin.india@rediffmail.com

8-bit Microcontrollers

Microchip has expanded its PIC18 product line with the addition of 8-bit K83 microcontrollers (MCUs) that combine a controller area network (CAN) bus with an extensive array of core independent peripherals (CIPs). A



key advantage of using a K83 MCU in CAN-based systems is that CIPs provide deterministic response to real-time events, shorten design time and can be easily configured through the MPLAB Code Configurator (MCC) tool. The new family is ideal for applications using CAN in the medical, industrial and automotive markets, such as motorised surgical tables, asset tracking, ultrasound machines, automated conveyors and automotive accessories.

Microchip
www.microchip.com/k83

Diode

Littelfuse, Inc. has introduced AEC-Q101-qualified TVS diodes to



protect sensitive automotive circuitry from damaging surges and electrostatic discharges. Combining up to 600 watts of peak pulse power dissipation with fast response, the TPSMB series automotive TVS diodes offer circuit designers a high-voltage, single-component circuit protection solution. With a standoff voltage range of 10V to 550V for both unidirectional and bidirectional forms, the series is ideal for protection of I/O interfaces, Vcc bus and other vulnerable circuits.

Littelfuse, Inc.
www.Littelfuse.com

Microcontrollers

Renesas Electronics Corporation has expanded its RX65N/RX651 lineup with the addition of MCUs featuring integrated Trusted Secure IP, and enhanced flash protection and human-machine interface (HMI) for industrial and network control systems. The expanded RX65N/RX651 devices create a secure and stable integrated solution, as proven by the Cryptographic Algorithm Validation (CAVP)