

Multipurpose AC/DC power supplies for harsh environments and mission critical applications


KAN5000, 5 kW

FEATURES

- Input voltage 220, 380 VAC or 300 VDC
- Output voltage up to 300 VDC; Efficiency up to 94 %
- Wide voltage adjustment range 1–300 VDC
- Wide current adjustment range 0–100 %
- Digital control RS-485
- Hot-swap
- Operating temperature range up to –40 °C



Description of KAN5000:
<https://eng.kwsystems.ru/catalog/acdc/models/5.5>



<https://eng.kwsystems.ru>

KW SYSTEMS, LLC is a specialized manufacturer of a wide range of AC/DC power supplies, UPS, chargers and power systems ranging from 25 W to 100 kW. KW Systems offers modular low-profile units for defense applications, scaling high power platforms and DIN-rail mountable industrial PSUs designed for harsh environments.

Authorized Distributor in India:



Rebutor Electronics Pvt.Ltd
199/D First Floor, 4th Main, HAL 3rd Stage
Jeevan Bhima Nagar, Bangalore 560 075

Tel: +91-80-2526 1111 / 1122; Fax: 2526 1133
Email: info@rebutor.com / sales@rebutor.com
Web: www.rebutor.com

Flesh

SIVAA ENTERPRISES

334/1F, Agarwal School Road, King Puri Pinnu, Coimbatore-641108
Tamilnadu - India. Tel: 0422-6522072, Mob: +91-9842135781, +91-7373003781
Email: sales@fleshtrac.com, Web: www.fleshtrac.in

VEHICLE TRACKING SYSTEM



- Real Time Tracking and Positioning.
- Stolen Vehicle Recovery.
- Can View Average Speed and Distance Travelled.
- Stop, Idle, Run, Over Speed Alerts to the user through SMS.
- Inbuilt Battery Provides Backup for Two Days Even the Main Battery Power Supply is Cut.
- Five Registered User can get the details of the Vehicle.
- Tracking History Available for 3 Months.
- Android App Available.

TOKEN DISPLAY SYSTEM



QUEUE MANAGEMENT SYSTEM



- Best Queue Managing system and Token calling system.
- Token Display System available in Tamil, English, Hindi, Malayalam, Telugu & Kanada Languages.
- Random Calling & Sequential calling Available.
- Both Wired & Wireless systems are Available.
- Single line Display and Multi line Display are Available.
- Can be effectively used in Canteens, Banks, Hotels & any office that follows a Queue System.



IoT we GoT this... Wireless Embedded Starts Here!

Dual-Mode Bluetooth
Classic 3.0 &
BLE 4.2 : BT53



- Bluetooth Classic 3.0 & BLE 4.2; dual mode
- Size: 11.6 x 13.5 mm
- RF Tx/Rx: +12 dBm, -82 dBm
- Supports data and audio applications
- Supports Apple iOS, iPad2 profile and Android

Low Cost
Standalone BT
Module : BT24



- Class 1.5, Bluetooth 3.0
- Size: 15 x 20 mm
- RF Tx/Rx: +6 dBm, -88 dBm
- Supports data and audio applications
- Supports Apple iOS/Android

WiFi Standalone
IoT Module : WF-43



- 802.11 b/g/n
- Size: 14.6 x 13.5 mm
- Host MCU included
- Supports Wi-Fi direct and Soft AP

Please Contact for Further Details :

**HARIHI OHM
ELECTRONICS**

Flat No.G2, Sai Heights, Plot No.59-63,
New Reddy Enclave, Old Alwal,
Secunderabad - 500 010 India
Ph: 09246330299, Email: info@harihiom.in
Web: www.harihiom.in

Amped RF
TECHNOLOGIES

Amped RF Technology, Inc.
2674 North First Street, #220
San Jose, CA 95134, USA
Web: www.ampedrftech.com