



PREMIUM 3D PRINTER FILAMENTS

Small spool sizes so you can experiment with more colors without spending a bundle!
• 0.25kg spools
• 0.50kg spools



ENCAPSULATING AND POTTING EPOXIES



SILVER CONDUCTIVE EPOXY

Cat. No. 8331

Cold Solder Repair

Now available in
40 gram kits!



PENETRATING OIL

Cat. No. 8472



TOTAL GROUND

Carbon Conductive Coating

Cat. No. 838

Create your own
static-free work station



ACRYLIC CONFORMAL COATING

IPC-CC-8308

Cat. No. 419C



Flux Removers



Contact Cleaners



Circuitboard Protection



Coatings



EMI/RFI Shielding



No Clean Flux



Distributed in India by :

PROGRESSIVE ENGINEERS

C-228A, Ghatkopar Industrial Estate, Amrut Nagar, Off LBS Marg, Ghatkopar (West), Mumbai - 400 086, Maharashtra.
T: 022-2500 6762 Vapi Off.: 0260-2451744 E: info@progressiveengineers.net W: www.progressiveengineers.net

High voltage and long life aluminum electrolytic capacitors that support highly reliable power sources and lighting equipment.

LIFE SPAN MAXIMUM GUARANTEE 20000 105° C

HK

- Voltage: 160~450V
- Capacitance: 1~68
- Endurance: 105° C 20000hours(160~450V)
- Size: ϕ 6.3 x 12 to ϕ 18 x 32

Application: LED Lighting Devices



[Development background]

Due to the long life of LED light-emitting diodes, LED lighting equipment further longevity demands electrolytes of high reliability, product design optimization to achieve.

Meet the demands of high-voltage range, products cater to a wide range of user requirements.

HK

Life time
doubles

105° C 20000hours

HD

105° C 10000hours

● When it is assumed the LED lighting is only the life of capacitor



ZHAOQING BERYL ELECTRONIC TECHNOLOGY CO.,LTD

Mail: fsale12@zq-beryl.com Mobile: +86-18125261329 <http://www.zq-beryl.com>