

The Best Value in Electronic Test & Measurement

SDM3045X Series Digital Multimeter



- Real 4½ digit (60000 count) readings resolution
- Up to 150 rdgs/s measurement speed
- True-RMS AC Voltage and AC Current measuring
- 1 Gb NAND flash size, Mass storage configuration files and data files
- With easy, convenient and flexible PC software: EasyDMM
- Standard interface: USB Device, USB Host, LAN
- USB & LAN remote interfaces support common SCPI command set. Compatible with other popular DMMs on the market

SDG1000X Series Function/Arbitrary Waveform Generator

Product Model	SDG1032X	SDG1062X
Bandwidth	30 MHz	60 MHz
Sampling rate	150 MSa/s	
Vertical resolution	14-bit	
Waveform Length	16 kpts	
Display	4.3" display, 480 x 272 x RGB Standard: USB Host, USB Device, LAN Optional: GPIB (USB-GPIB adaptor)	
Interface		



SDS2000X Super Phosphor Oscilloscope

Models	SDS2072X SDS2074X	SDS2102X SDS2104X	SDS2202X SDS2204X	SDS2302X SDS2304X
Bandwidth	70 MHz	100 MHz	200 MHz	300 MHz
Real-time sampling rate	2G Sa/s			
Channels	2/4 + EXT			
Memory depth	140 Mpts			
Trigger Type	Edge, Slope, Pulse width, Window, Runt, Interval, Dropout, Pattern, Video			
Serial Trigger	IIC, SPI, UART/RS232, CAN, LIN			
16 Digital Channels (MSO Option)	Maximum waveform capture rate up to 500 MSa/s, Record length up to 140 Mpts/CH			



SSA3000X Series Spectrum Analyzer

Model	SSA3021X	SSA3032X
Frequency Range	9 kHz~2.1 GHz	9 kHz~3.2 GHz
Resolution Bandwidth	10 Hz~1 MHz, in 1-3-10 sequence	
Displayed Average Noise Level	-161 dBm/Hz, Normalize to 1 Hz (typ.)	
Phase Noise	<-98 dBc/Hz@1 GHz, 10 kHz offset	



SIGLENT TECHNOLOGIES CO., LTD.

Add: Blog No.4 & No.5, Antongda Industrial Zone, 3rd Liuxian Road, Bao'an District, Shenzhen, 518101, China.
Tel: + 86 755 3661 5186, Email: sales@siglent.com, Website: http://www.siglent.com/eng/.

SIGLENT®