

NEW PRODUCTS

MAKE IN INDIA

TEST & MEASUREMENT

Test probe

Anritsu expands its field test portfolio with the introduction of PIM Hunter, a passive inter-modulation test probe that helps field technicians more



quickly discover the precise location of external PIM sources at cell sites. Designed for use with Anritsu's PIM Master, Spectrum Master and BTS Master handheld analysers, PIM Hunter test probe enables field professionals to use traditional interference hunting techniques to accurately locate external PIM sources for optimum wireless network performance.

Anritsu India Pvt Ltd
www.anritsu.com

Imaging multimeter

FLIR DM284 imaging multimeter with IGM is a professional, all-in-one true-RMS digital multimeter with built-in 160 x 120 FLIR thermal imager that can show you exactly where an electrical problem is, to speed up troubleshooting. DM284 visually guides you to the precise location of an electrical problem and helps you to pinpoint hot-spots faster and more efficiently. Other features include VFD mode, LoZ, NCV, test probes and type K thermocouple input.



FLIR Systems India Pvt Ltd
www.flir.in

Dust density meter

Toshniwal Sensing Device offers a dust density meter, DDM-fc, for effective detection and measurement of dust. This system is developed for high temperature conditions such as in India. It automatically measures dust density continuously as relative density using the light-scattering method. This method allows continuous measurement and display of relative density proportional to the quantity of dust. It is an air-contamination monitoring instrument with current output (4-20mA) and RS232C output.

Toshniwal Sensing Devices Pvt Ltd
www.tsdp.com

Temperature controller

Key features include:

- Universal measuring input
- Digital input filter: timer settable from 0 to 999.9 seconds
- Control type: PID and on/off
- Onsite mode selection: auto/manual
- Timer function with five functional selections
- Onsite programmability: heating/cooling
- Output on failure function



Rishabh Instruments
www.rishabh.co.in

Oscilloscope

NI has announced PXIe-5164 oscilloscope, which includes a user-programmable FPGA to help aerospace/defence, semiconductor and research/physics applications that require high-voltage measurements and high levels

of amplitude accuracy.

Features of PXIe-5164 are:

- Two 14-bit channels sampled at 1GS/s with 400MHz bandwidth
- Two category II-rated channels with voltage input range up to 100Vpp with programmable offsets allowing measurements up to $\pm 250V$
- Up to 34 channels to build parallel, high-channel-count systems in a compact form factor
- 3.2GB/s streaming data rate enabled by eight lanes of PCI Express Gen 2 bus communication



National Instruments
www.ni.com

COMPONENTS

Microcontroller

MAX32560 embeds all security features required to address stringent PCI-PTS requirements including active tamper protection, scrambling keypad for pin handling and a secure cryptographic engine. It integrates a number of analogue interfaces to reduce the PCB footprint, including a full EMV contactless reader interface, two EMV smartcard interfaces, a DSP based high-performance magnetic stripe reader, two-channel analogue-to-digital converter and a digital-to-analogue converter.



Maxim Integrated
www.maximintegrated.com

Connector

Mil-spec connectors (entire MIL-C-5015 series) are in accordance with