

military specifications. Coupling can be of straight plug, angled plug, cable



plug, thru-bulkhead, box-mount receptacle and bayonet types.

Indian Sales Corp.
indiansalescorp@gmail.com

Thermal printer mechanism

The thermal printer mechanism is pin-to-pin compatible with Fujitsu FTP-638 MCL101/MCL103. Specifications are as follows:



- Printing method: Thermal dot-line printing
- Dots/line: 576
- Resolution: 8 dots/mm
- Printing width: 72mm
- Paper width: 76mm to 80mm
- Feed resolution: 0.125mm
- Operating temperature: 0°C - 40°C
- Operating humidity (RH): 20% to 80%

Rajguru Electronics
www.rajguruelectronics.com

Multi-sensor module

STMicroelectronics' 13.5mm x 13.5mm SensorTile is the smallest turnkey sensor board of its type, containing a MEMS accelerometer, gyro-



scope, magnetometer, pressure sensor and MEMS microphone. With the onboard low-power STM32L4 microcontroller, it can be used as a sensing and connectivity hub for developing products such as wearables, gaming

accessories and smart home or Internet of Things (IoT) devices.

STMicroelectronics
www.st.com

Flash memory cells

Renesas Electronics has announced the world's first split-gate metal-oxide nitride oxide silicon (SG-MONOS) flash memory cells employing transistors with fin shape for use in microcontrollers with on-chip flash memory having a circuit line width of 16 to 14 nanometres (nm) or finer. SG-MONOS technology is reliable for use in automotive applications.

Renesas Electronics Corp.
www.renesas.com

Peripheral touch controller

Microchip Technology has added an enhanced version of the periph-



eral touch controller (PTC) to their microcontrollers including ATtiny817/816/814. The PTC is a small and cost-effective core-independent peripheral that enables high-performance capacitive touch on standard microcontrollers. It features superior water tolerance, and is configured through START code configurator for ease-of-use.

Microchip Technology Inc.
www.microchip.com

MISCELLANEOUS

Systems on modules

Colibri iMX7S and Colibri iMX7D are SODIMM-sized systems on modules that are based on NXP/Freescale i.MX 7Solo and i.MX 7Dual systems on chips (SoCs), respectively. The

dual-core ARM Cortex-A7 runs a peak frequency of 1GHz, while the single-core ARM Cortex-M4 has a peak frequency of 200MHz.



In Colibri iMX7S, the single-core Cortex-A7 has a peak frequency of 800MHz, while the single-core Cortex-M4 runs at 200MHz. Both SoCs support asymmetric or heterogeneous multi-core processing, in which real-time applications can run on Cortex-M4, while user applications are taken care of by Cortex-A7. The SoCs consume very low power and support advanced security features.

Toradex Systems (India) Pvt Ltd
www.toradex.com

Heat transfer compound

Key features include:

- Very high maximum operating temperature (-68°C to +200°C)
- Good thermal conductivity
- High dielectric strength
- Non-bleeding
- Non-conductive
- Long service life
- Safe on plastics
- Provides excellent corrosion resistance

Progressive Engineers
www.progressiveengineers.co.in

Solar inverter

Servotech has launched a compact 12V, 100 watt, pure sine-wave solar inverter, with



MPPT charge controller conforming to IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-30, IEC 60529 and IEC 62093:2005 standards.

Main features are:

- Customised LCD with simultaneous display of PV voltage and current, battery voltage with status in