

Which is your favorite **X**-instrument ?

SDS2000X

Super Phosphor Oscilloscope

SDM3065X

Digital Multimeter

SDS1000X+

Super Phosphor Oscilloscope

SSA3000X

Spectrum Analyzer

SDG2000X

Arbitrary/Function
Waveform Generator

SPD3000X

Programmable Linear
DC Power Supply

SDS1202X-E

Super Phosphor Oscilloscope



SPO

EasyPulse

TrueArb

Phase noise
 $< -98\text{dBc/Hz}$

X-Scope

- 2 GSa/s sampling rate, 140,000 wfm/s
- 256-level intensity grading display
- Record length up to 140 Mpts
- Serial bus triggering and decode
- 10 types of one-button shortcuts

X-Source

- 4.3" touch screen display
- Innovative TrueArb technology, point-by-point architecture
- Innovative EasyPulse technology

X-Power

- 3 independently controlled and isolated outputs, total 220 W
- Supports front panel timing output functions

X-Spectrum

- Frequency range of 9 kHz to 2.1 GHz / 3.2 GHz
- -161 dBm/Hz displayed average noise level (Typ.)
- -98 dBc/Hz @10 kHz offset phase noise (1 GHz, Typ.)
- EMI pre-compliance measurements kit (Opt.)

X-Multimeter

- 4.3" TFT-LCD, 480*272
- 1 Gb nand flash size, mass storage configuration files and data files
- True-RMS AC voltage and AC current measuring
- Interface: USB Device, USB Host, LAN, GPIB and Scanner Card (Opt.)

SIGLENT TECHNOLOGIES CO., LTD.

Add: Bldg No.4 & No.5, Antongda Industrial Zone, 3rd Liuxian Road, Bao'an District, Shenzhen, 518101, China.
 Tel: + 86 755 3661 5186; Email: sales@siglent.com; Website: http://www.siglent.com/ens/

 **SIGLENT**®