

measurement. It also has a timer for PV insulation testing, and logging and PC interface for record keeping. Waterproof design (IP54 standard) enables measurement in bad weather conditions. The tester has on-board memory logging for up to 1000 datasets.

Kyoritsu KEW India Instruments
www.kew-ltd.co.in

Handheld thermal imaging camera

Meco's handheld thermal imaging camera TIC300 combines both surface temperature measurement and real-time thermal imaging functions. Unlike traditional thermal imaging cameras that measure components one by one, TIC300 does it together, thus saving users' time.

The meter has a 6cm (2.4-inch) colour display with a resolution of 60x60. Temperature range is -20°C to 300°C. The meter comes with various colour palettes like iron red, rainbow, rainbow high contrast, grey scale (white glow) and grey scale (black glow).

Meco Instruments
www.mecoinst.com

Digital multimeter

Siglent's SDM3065X is a 6½-digit (2,200,000-count) multimeter with dual display. Suited for high-precision, multifunction and automatic measurement, it has a powerful testing engine, 1Gb NAND flash size, mass storage configuration files and data files,



historical data, and external U disk storage. Interfaces include USB device, USB host and LAN.

Siglent
https://www.siglent.eu

COMPONENTS

SMD LEDs

LEDChip Indus has released 1W, 150mA SMD LEDs with 145 lumens/watt output that deliver exceptional brightness, thanks to their specially designed lead frame profile and improved heat dissipation. The KLSL2835W LEDs are claimed to be the world's lowest priced LED types for a given wattage; lower than the 5630/5730 SMD LEDs.



LEDChip Indus Pvt Ltd
www.LEDChip.in

Surface-mount fuse

Littelfuse, Inc. has introduced an encapsulated surface-mount fuse for intrinsic safety protection of equipment used in or near hazardous locations and explosive atmospheres. During over-current and short-circuit conditions,



the 1mm-thick encapsulation around the body of the PICO 304 series surface-mount fuse minimises the amount of heat produced and contains any sparks or arcs inside the fuse assembly, preventing them from being exposed to potentially explosive gases or dust in the environment. This encapsulation eliminates the need to pot or coat printed circuit boards or assemblies, saving production time and money.

Littelfuse, Inc.
www.Littelfuse.com

Automotive LED controller

The MAX20078 synchronous buck, high-brightness LED controller from



Maxim Integrated Products provides both fast response and low electromagnetic interference (EMI) for exterior LED lighting and improved safety applications. Ideal for matrix lighting designs, it allows designers to achieve high performance, ease of design and fast time-to-market. While eliminating the need for external compensation components, it also features a wide dimming ratio, and integrated fault protection and monitoring circuitry.

Maxim Integrated
https://www.maximintegrated.com

Surface-mount low-power modules

STMicroelectronics has added five space-saving surface-mount intelligent power modules to its SLIMM-nano family, giving the choice of IGBT or MOSFET outputs for in-motor or other space-constrained drives all the way from very low power ratings up to 100W. The new modules deliver high conduction and switching efficiency, especially in hard-switching circuits at frequencies up to 20kHz. The integrated gate-driver circuitry minimises EMI by managing switching voltage and current slopes.



STMicroelectronics
www.st.com

Fuse holders

SCHURTER has introduced FUS series dust- and water-proof fuse hold-