

Metrix⁺
Innovative Excellence

Test & Measuring Instruments

Metrix⁺ DM 620
50000 Count Data
Logger DMM DOT
MATRIX LCD Display
with 42 Segments
Bar Graph



- International Safety Standard IEC 1010-1 (EN 61010-1:1993) Over Voltage
- Category II & III
- 0.05% of basic accuracy
- DM620: 50,000 count of high resolution
- Isolated USB Interface & Isolated USB Battery Charger
- Data Logger Memory: 18,000 Points
- Function and ranges may be controlled from PC via USB.
- True RMS measurements for AC

- Full Auto Range**
- Auto Calibration
- Auto power off
- Data holds and run mode
- Low battery indication
- Overload protection for all functions (including 10A)
- Relative (REF, DEF, REL) mode
- Compare (CO-NOSC) Mode and Trend Plot
- Real Time Clock and Date, Multi display
- Back light display
- 1000V AC, DC measurement
- 10 Mhz frequency counter
- Period, Duty cycle measurement
- 20M resistance and Capacitance measurement
- Continuity and Diode test (temperature °C/°F) using "K" type thermocouple
- Room temperature without any
- temperature probe
- 10A AC, DC measurement

Metrix⁺ 18 TRMS
TRUE RMS
6000 Count 3.6/7
digit DMM
Large Back light
LCD Display Auto
Auto Range



- International Safety Standard IEC 61010-1
- Dual Insulation
- DCV 600mV ~ 1000V +0.8% (+5d)
- ACV 600mV ~ 700V +1.2% (+5d)
- ACA/DCA 60A ~ 10A +2% (+5d)
- Resistance 600W ~ 60MW +1% +5d
- Capacitance 10nF ~ 10mF +3% +5d
- Frequency 10Hz ~ 10mHz +0.5% +3d
- Duty Cycle 1% ~ 99% +0.5% +3d
- Temp. C/F -50°C ~ 1000°C +1.5%
- Diode, Continuity
- Power SW (6FZ2) battery Data Hold, Max/Min Value Hold
- Auto power off

Metrix⁺ 451 LCR
Multimeter
1999 Count 3 1/2 digit
digit DMM
Large Back light LCD
Display Panel calibrate



- Panel Calibrate LCR DMM 3 1/2 Digit, MAX Display: 1999
- Over Load Protection
- Large LCD Back light, Function characters
- Indication
- DCV: 200mV/200V ±0.5% ±5, 1000V ±0.8% ±5
- ACV: 2/200V ±0.8% ±5, 700V ±1.2% ±7
- DCA: 2mA ±0.8% ±5, 20mA ±1.2% ±5, 10A ±2% ±5, ACA: 200mA ±1.8% ±5, 10A ±3% ±5
- RESISTANCE: 200 ±1% ±5, 2k/200k/2M ±0.8% ±5, 20M ±1.5% ±5
- CAP: 20n/200n/2uF ±3% ±5, 200uF ±5% ±10
- FREQ: 2k/200k/200k ±0.5% ±3
- INDUCTANCE: 2mH ±3% ±5, 20m/200m/20H ±3% ±5
- CONTINUITY BUZZER
- DIODE
- TRANSISTOR HFE
- POWER SUPPLY: 6FZ2 or NEDA9V-1

minoo Impex

41, N.S.Road, 206, Anand Jyoti,
KOLKATA 700001, INDIA.
Tel: +91 33 2230 9888 Fax: +91 33 2230 9719
E-mail: minooimpex41@vsnl.net
metrixinstrument@gmail.com
www.metrixinstrument.com

PUNE - M/S. Metrixplus Instruments (PUNE)
Tel: 02024379992 • e-mail: metrixplus@hotmail.com
• metrixinstruments@yahoo.com

Chennai - M/S. Mehta Doshi & Company
Tel: 044 25341892 • e-mail: mehtadoshi@gmail.com

Ahmedabad - M/S. Bearing & Tools Centre
Tel: 07965458950 • e-mail: info@bearingtoolcentre.com

Delhi - M/S. Chand Company
Tel: 011 23213236 • e-mail: info@chandcompany.com

www.opensourceforu.com

An
EFY GROUP
MAGAZINE

Open
Source
Is **Hot**
In The
IT World

Hadoop
Apache
Android
MySQL
JSS
PEARL
OpenStack
Joomla
Drupal
PHP

**THE COMPLETE
MAGAZINE
ON OPEN
SOURCE**

OpenSource
5
Amazing
SysAdmins

» To find dealers to buy copy from news-stand,
visit: www.ezine.efymag.com

» To subscribe, visit: pay.efyindia.com

» To buy an ezine edition,
visit: www.magzter.com choose Open Source For You