

SMD DC/DC Converters 1 - 15 Watt

- MSL Level 2 or better
- Operating temperature -40 ~ +85°C
- 1500 VDC I/O-isolation (standard)
- Single and dual output models
- Washable models on request
- Available in tape & reel package

TES 1 1 WATT • 3.3 to 15 VDC (unregulated) • $\pm 10\%$ Input 5, 12, 24 VDC • 13.7 x 8.0 x 7.0 mm 	TES 1V 1 WATT • 3000 VDC I/O-isolation • 3.3 to 15 VDC (unregulated) • $\pm 10\%$ Input 5, 12, 24 VDC • 16.3 x 8.0 x 8.0 mm 	TRN 1SM NEW 1 WATT • 3.3 to 24 VDC • 2:1 Input 4.5 to 75 VDC • IEC/UL 60950-1 • 11.9 x 11.3 x 8.0 mm 
TDN 1WISM NEW 1 WATT • 3.3 to 24 VDC • 4:1 Input 4.5 to 75 VDC • Remote On/Off • 13.2 x 9.1 x 10.2 mm 	TMR 1SM 1 WATT • 5.0 to 24 VDC • 2:1 Input 4.5 to 75 VDC • 18.9 x 13.7 x 8.7 mm 	TES 2H 2 WATT • 3.3 to 15 VDC (unregulated) • $\pm 10\%$ Input 5, 12, 24 VDC • 16.3 x 8.3 x 8.9 mm 
TMR 2WISM NEW 2 WATT • 5.0 to 15 VDC • 4:1 Input 4.5 to 75 VDC • Remote On/Off • IEC/UL 60950-1 • 19.0 x 14.9 x 8.7 mm 	TDR 2(W)SM 2 WATT • Epoxy over mold (washable) • 5.0 to 15 VDC • 2:1/4:1 Input 4.5 to 75 VDC • Remote On/Off • IEC/UL 60950-1 • 18.9 x 12.8 x 8.7 mm 	TES 2N 2 WATT • EN 55022 class A filter • 3.3 to 15 VDCxxx • 2:1 Input 4.5 to 75 VDC • IEC/UL 60950-1 • 24.0 x 13.7 x 9.3 mm 
TES 2M 2 WATT • 4 kWAC I/O-isolation • 5.0 to 15 VDC (unreg.) • $\pm 10\%$ Input 5, 12, 24 VDC • IEC/UL 60950-1, 60601-1 • 24.0 x 13.7 x 9.3 mm 	TRN 3SM NEW 3 WATT • 3.3 to 24 VDC • 2:1 Input 4.5 to 75 VDC • IEC/UL 60950-1 • 11.9 x 11.3 x 8.0 mm 	TDN 3WISM NEW 3 WATT • 3.3 to 24 VDC • 4:1 Input 4.5 to 75 VDC • Remote On/Off • Compact design • 13.2 x 9.1 x 10.2 mm 
TMR 3WISM NEW 3 WATT • 5.0 to 24 VDC • 4:1 Input 4.5 to 75 VDC • Remote On/Off • IEC/UL 60950-1 • 19.0 x 14.9 x 8.7 mm 	TDR 3(W)SM 3 WATT • Epoxy over mold (washable) • 5.0 to 24 VDC • 2:1/4:1 Input 4.5 to 75 VDC • Remote On/Off • IEC/UL 60950-1 • 18.9 x 12.8 x 8.7 mm 	THL 3 WISM 3 WATT • EN 55022 class A filter • 3.3 to 24 VDC • 4:1 Input 9 to 75 VDC • Remote On/Off • IEC/UL 60950-1 • 24.0 x 13.7 x 9.3 mm 
TDN 5WISM NEW 5 WATT • 3.3 to 24 VDC • 4:1 Input 4.5 to 75 VDC • Remote On/Off • Compact design • 13.2 x 9.1 x 10.2 mm 	THL 6WISM 6 WATT • EN 55022 class A filter • 3.3 to 24 VDC • 4:1 Input 9 to 75 VDC • Remote On/Off • IEC/UL 60950-1 • 22.0 x 20.3 x 10.2 mm 	TON 15(W)SM 15 WATT • EN 55022 class A filter • 3.3 to 15 VDC adjust. • 2:1/4:1 Input 9 to 75 VDC • Remote On/Off • IEC/UL 60950-1 • 27.9 x 23.9 mm 

Authorized Distributor in India:



REBUTOR ELECTRONICS PVT.LTD

199/D First Floor, 4th Main, HAL 3rd Stage
 Jeevan Bhima Nagar, Bangalore 560 075, India
 Tel: +91-80-2526 1111 / 22 / 33; Cell: 8904011135 / 38
 Email: info@rebutor.com / sales@rebutor.com
 Web: www.rebutor.com