


Product Characteristics

- Accurate voltage and current measurement capability, low noise output
- Constant Power and wide range of voltage and current output
- Master/Slave parallel and series operation model for up to 10 units
- Built-in standard automobile electrical test curve with 2U type products
- Ultrafast output load transient response time (1.5ms) and command response time (50ms)
- Standard communication interface RS232/RS485/USB/LAN, GPIB is optional
- Full safety (CSA,UL,CE,ROHS) and EMI compatibility (CE,FCC) certifications
- OVP/OCP/OPP/OTP/SCP

DC Power Supply

600W/1000W	20V/32V/40V
/1200W/1500W	/60V/75V/80V
/1600W/2000W	/120V/150V/200V
/3000W/4000W	/400V/600V/800V



2U



APM Technologies (Dongguan) Co., Ltd



overseas@apmtech.cn



en.apmtech.cn

Trusted The Leader & You want to Cover Your Bad Purchases

Talk to The Phase Coherent Experts, Call **VigVen +91-80- 2333-9220**

- Industry Leading Phase Noise & Spectral Purity: <-80dbc Spurious.
- Ultimate in Frequency Accuracy, Channel-To- Channel
- Calibrated Dynamic Range: +23dBm to -110dBm.
- Phase Coherent, 100% Independently Tunable Channels. Stability and Phase Coherent Channels.
- Excellent fit for TDOA, AOA applications.

VIGVEN SOLUTION



COMPETITOR



Highest channel density: 64 channels: 0.125m³	?
Ultra-Low Phase Noise: -131dBc/Hz at 1GHz, 10kHz Offset	-128dBc/Hz at 1GHz, 10kHz Offset
Fine Tuning Resolution: 0.001Hz, 0.1degree, 0.1dBm	?
Thermal Phase Drift: < 1.0 degree over 12hours	?
Output Power Range: -110dBm to +13dBm (0.1dB steps)	-135 to +15 dBm
Fully Independent, standalone channel control	Control of independent boxes
USD 200K	USD 700K