



DOUBLE THE SCOPE AT HALF THE PRICE

SDS1000X-E Series Super Phosphor Oscilloscope

- 200 MHz Bandwidth
- 1 GSa/s Real-time Sampling Rate
- True measurement and math to all of sample 14 M points
- 1 M points FFT
- Serial bus triggering and decode (Standard)

Model	SDS1202X-E
Bandwidth	200 MHz
Sampling Rate (Max.)	1 GSa/s
Channels	2+EXT
Memory Depth (Max.)	7 Mpts/CH (Dual-Channel); 14 Mpts/CH (Single-Channel)
Waveform Capture Rate (Max.)	100,000 wfms/s (normal mode), 400,000 wfms/s (sequence mode)
Trigger Type	Edge, Slope, Pulse Width, Window, Runt, Interval, Dropout, Pattern, Video
Serial Trigger (Standard)	IIC, SPI, UART/RS232, CAN, LIN
Decode Type (Standard)	IIC, SPI, UART/RS232, CAN, LIN
I/O	USB Host, USB Device, LAN, Pass/Fail, Trigger Out
Probe (Std)	2 pcs passive probe PP215
Display	7 inch TFT-LCD (800x480)
Weight	Without package 2.5 Kg; With package 3.5 Kg

I AM X-MULTIMETER!

SDM3065X Digital Multimeter

- Real 6 1/2 digit readings resolution (2,200,000)
- True-RMS AC Voltage and AC Current measuring
- Built-in cold terminal compensation for thermocouple
- With easy, convenient and flexible any sensor measurement control software: EasyDMM
- Standard interface: USB Device, USB Host, LAN
- Supports GPIB and Scanner Card (Optional)



SIGLENT TECHNOLOGIES CO., LTD.

Add: Blog No.4 & No.5, Antongda Industrial Zone, 3rd Liuxian Road, Bao'an District, Shenzhen, 518101, China.
Tel: +86 755 3661 5186; Email: sales@siglent.com; Website: http://www.siglent.com/ens/.

