

protocol analysis, an arbitrary waveform generator, a digital multimeter, a programmable DC power supply and digital I/O. The device features are simple, convenient and provide more efficient circuit design, debugging and validation. The included software lets you view all measurements on a single screen.

National Instruments
www.ni.com

Temperature and humidity recorder

This newly-released temperature and humidity recorder, HT20, is equipped with Ethernet interface for connection to a local or global network (LAN or WAN).

Through an intuitive and friendly-to-use Web server, you can always have access to information about measured values, status of the device, configuration of device and device information such as serial number, code execution, software and bootloader version.

Rishabh Instruments Pvt Ltd
www.rishabh.co.in

Phase sequence indicator

Meco's latest phase sequence indicator is used to determine phase sequence R, Y and B of three-phase voltages.



Features are:

- Three-phase sequence indication
- Reverse-phase indication
- Open-phase indication

- Coloured test probes with heavy-duty insulated crocodile clips for R, Y and B phase connections
- Phase presence indication from 60V AC (PH-N)

Meco Instruments Pvt Ltd
www.mecoinst.com

Multimeter

Model-702 is a new, low-cost, multi-functional digital multimeter that has a 3½-digit, 1999-count LCD display. It is an average-sensing digital multimeter with 0.8 per cent DC voltage basic accuracy. It can measure:

- DC voltage ranges from 100µV to 1000V in five steps, that is, 200mV, 2V, 20V, 200V and 1000V
- AC voltage ranges from 100µV to 750V in five steps, that is, 200mV, 2V, 20V, 200V and 750V
- DC/AC current ranges from 100µA to 10A in five steps, that is, 200µA, 2mA, 20mA, 200mA and 10A
- Resistance ranges from 0.1Ω to 20MΩ in six steps, that is, 200Ω, 2kΩ, 20kΩ, 200kΩ, 2MΩ and 20MΩ
- Capacitance ranges from 1pF to 20µF in five steps, that is, 2nF, 20nF, 200nF, 2µF and 20µF



Kusam Electrical Industries Ltd
www.kusamelectrical.com
www.kusam-meco.co.in

COMPONENTS

CAN bus transceiver modules

The recently-introduced TD301MCAN and TD501MCAN series are cost-effective CAN bus transceiver modules that integrate power isolation, signal isolation, CAN transceiver and bus protection in one module. The series convert TTL/CMOS level to difference level of CAN bus to achieve signal iso-

lation. Moreover, the modules feature 2500V DC electric isolation and a miniature package that enable these to be better embedded in a device to achieve connectivity functions of a CAN bus network.



Mornsun Guangzhou Science & Technology Co. Ltd
www.mornsun-power.com

Power modules

Texas Instruments has introduced a pair of 12V, 10A, 4MHz step-down power modules that provide a power management solution that is 20 per cent smaller than any other 10A



power module based solution available today. The easy-to-use SWIFT TPSM84A21 and TPSM84A22 DC/DC modules integrate power MOSFETs, shielded inductors, input and output capacitors, and passives into a tiny, low-profile footprint. These also provide one per cent overshoot in transient conditions without special magnetics or additional capacitors.

Texas Instruments Inc.
www.ti.com

PWM controller

BP3319MB is a new, high-precision primary-side regulation PWM controller with single-stage active PFC, specially designed for universal input offline flyback or buck-boost constant current LED lighting. The controller with on-chip PFC circuit achieves high power factor and low THD. Operating in critical conduction mode, the power MOSFET switching loss is reduced and the inductor is fully utilised. BP3319MB adopts the proprietary primary-side current-sensing scheme. It can precisely control LED currents