

NEW PRODUCTS

MAKE IN INDIA

TEST & MEASUREMENT

Oscilloscope

SIGLENT's new SDS1000X-E series super phosphor oscilloscope is available in one bandwidth, 200MHz. It has a maximum sample rate of

1GSa/s and a standard record length of 14Mpts. For ease-of-use, the most commonly used functions can be accessed with its user-friendly front panel design.

The SDS1000X-E series employs a new generation of super phosphor oscilloscope technology that provides excellent signal fidelity and performance. It comes with a minimum vertical input range of 500µV/div, an innovative digital trigger system with high sensitivity and low jitter, and a waveform capture rate of 400,000 frames/sec (sequence mode).

Siglent Technologies Co. Ltd
www.siglent.com

Digital lux meter

The new digital lux meter (model 930T) from Mecco comes with a flexible

sensor that can be used to measure light intensity of even remote places where a human hand cannot reach. It

comes with user-selectable units of lux and fc from range 0.1 - 200,000 lux and 0.0 - 20,000 fc with special functions, namely, Max, Min, Backlight and Auto Power Off with Disable and Data Hold features. It is widely used because of its portability, light weight and accuracy.

Meco Instruments Pvt Ltd
www.mecoinst.com

DC-milli-ohm meter

Kusam-Meco has introduced a DC-milli-ohm meter that has 4½-digit LED display with comprehensive parameter indication, which makes the reading clear and simple. Readings can be taken during the day and in the dark.

Due to its simple design, it is very easy to operate. It has eight measuring ranges, namely, 20mΩ, 200mΩ, 2Ω, 20Ω, 200Ω, 2kΩ, 20kΩ and 200kΩ, with an accuracy of 0.05% + 2 digits. It features very high stability and gives accurate readings owing to four-wire measurements. Its unique feature is that percentage error is selectable in three steps: one, two and three per cent. Auxiliary power required is AC 220V ± 10%.

Kusam Electrical Industries Ltd
www.kusamelectrical.com,
www.kusam-meco.co.in

Multichannel power probe

The new R&S RT-ZVC02/04 multichannel power probe can measure across large current and voltage ranges with-

out having to switch ranges, making it possible to monitor the power consumption of chipsets, radio modules and wearables such as smartwatches.

When used in combination with an R&S RTE or R&S RTO oscilloscope, the current drain can be clearly correlated with analogue and digital control signals, enabling developers to optimise the battery life of such wearables and wireless devices early in the development cycle.

Rohde & Schwarz
www.rohde-schwarz.com

Wireless connectivity test set

Anritsu has introduced MT8862A instrument with industry-first network mode for evaluating IEEE802.11ac WLAN devices.

This new model strengthens the company's products for testing WLAN equipment.

With built-in communication protocols supporting IEEE802.11ac/n/a/g/b as standard, MT8862A uses network mode to measure the performance of the target WLAN device under test in the actual operating state. RF performance characteristics such as Tx power and Rx sensitivity (PER) can be measured using this network mode, which helps with the configuration of a simpler test environment and eliminates the need for dedicated vendor-provided test modes required for WLAN device inspections.

Anritsu India Pvt Ltd
www.anritsu.com

Fuel gauge

MAX17055 is a new, low-7µA operating current fuel gauge that implements Maxim ModelGauge m5 EZ algorithm. ModelGauge m5 EZ makes fuel gauge implementation easy by eliminating battery characterisation requirements and simplifying host software interaction. ModelGauge m5 EZ robust algorithm provides tolerance against battery diversity for most lithium batteries and applications.

MAX17055 provides precision measurements of current, voltage and temperature. Temperature of the battery pack is measured using an internal temperature measurement or external thermistor. A two-wire I2C interface provides access to data and control registers.

Maxim Integrated
www.maximintegrated.com