

## Datamate – Performance without compromise.



Harwin is a manufacturer of standard interconnect components with an enviable reputation for high quality and customer service. The company is best known for the high-reliability Datamate range. Offering high performance and approved to British Standard 9525-F0033, the range has a proven track record for performance under extreme conditions.

The 2mm pitch solution is available in all variations of cable-to-board, board-to-board and cable-to-cable within the connector family. Options cover single, dual and triple row configurations with both vertical and horizontal orientations for PCB design flexibility.

The proven 4-finger contact clip ensures the integrity of connection under the most severe conditions, making Datamate ideally suited to all applications subject to high loads of vibration and shock. The Beryllium Copper contact material provides excellent spring force and increased durability within an improved temperature range of -55°C to +125°C.

With the addition of the Datamate Mix-Tek family, the 3A signal contacts can be supplied in the same connector as 20A power, 40A high power or 6GHz coax contacts, giving complete flexibility of design.

### Product Families

- **Datamate Mix-Tek:**  
3 connector styles in one. Includes low frequency signal, power (20A), high power (40A) and coax (6GHz) options. A stocked range of coax-only, power-only, high-power-only, or mixed power and signal connector, ideal for COTS requirements.
- **Datamate J-Tek:**  
101Lok hardware connectors with variety of optional jackscrews for increase security of connection. Includes 2-row and 3-row configurations.
- **Datamate 101Lok:**  
101Lok hardware reduces assembly time by simplifying the mating process. The fast mate hardware requires 101-degree turn to securely mate and requires no special tooling.
- **Datamate L-Tek:**  
Datamate low frequency connectors with 3 flexible mating options: friction latch, locking latch and no latch. Includes 1-row and 2-row configurations.