



NEW PRODUCTS

MAKE IN INDIA

COMPONENTS

Switching regulators

MORNSUN's new SMD-packaged K78T-500R3/K78T-1000R3 series non-isolated



regulators meet the reflow soldering production requirements. The peak temperature

of reflow soldering is $T_c \leq 245^\circ\text{C}$ and keeps 60s (max.) above 217°C , meeting the IPC/JEDEC J-STD-020D.1 standard. Efficiency is up to 95 per cent and operating temperature ranges from -40 to $+85^\circ\text{C}$, without additional heat-sink.

Mornsun Guangzhou Science & Technology Co., Ltd.
www.mornsun-power.com

RF power detector

Analog Devices, Inc. has introduced a 9kHz-7GHz directional bridge and dual-RMS RF power detector that can simultaneously measure forward and reverse RMS power levels in a signal path along with return loss. The new ADL5920 detector represents a change to conventional approaches by integrating a directional bridge-based coupler that results in high levels of integration and bandwidth. For space-critical applications, the ADL5920 integrates coupling or sensing function with detection function and provides an output



that can drive a precision analogue-to-digital converter (ADC) directly. For wideband operation or for frequency variants, it eliminates the need to choose a different directional coupler for each frequency.

Analog Devices, Inc.
www.analog.com/ADL5920

Gate controller

Allegro MicroSystems, LLC has released a three-phase, sensorless, brushless DC (BLDC) motor controller for use with external n-channel power MOSFETs. The A4964 is specifically



designed for the automotive market, providing motor control functions in a system where a small microcontroller provides the communication interface to a central ECU and intelligent fault and status handling. It provides the supply and watchdog for the microcontroller, and high-voltage interfaces between the microcontroller and the central ECU and ignition switch. It can also operate as an independent single-chip remote motor controller.

Allegro MicroSystems, LLC
www.allegromicro.com

Bluetooth 5-compliant microcontroller module

u-blox has launched a full Bluetooth 5 compliant NINA-B3 wireless micro-

controller unit (MCU) module. Featuring Bluetooth low-energy long-range



connectivity, high data transfer rates and support for Bluetooth mesh and 802.15.4, NINA-B3 caters to applications in smart buildings, smart cities and the Industry 4.0, including smart lighting systems, industrial sensor networks, asset tracking solutions and building automation systems.

u-blox
www.u-blox.com

Power-line communication chipset

STMicroelectronics' new modular power-line communication (PLC) modem chipset provides more flexibility to manufacturers of utility meters, smart-grid nodes, streetlamps, and home and industrial controllers. The chipset



consolidates protocol handling to package and adapt data for transmission, and line driving for sending over mains wires. It enables customers to implement powerline communications cost-effectively, either as part of new designs or as the core of an add-on module on older devices.

The two-chip set comprises the ST8500 programmable PLC engine and STLD1 line-driver.

STMicroelectronics
www.st.com/powerline

Audio SoC

ROHM has introduced a high-resolution audio SoC designed to act as the 'brain'