

The Best Value in Electronic Test & Measurement



TG
FREE

New Pricing and Free Enhancements on the SIGLENT SSA3032X!

Model	SSA3032X New Pricing	SSA3021X
Frequency Range	9 kHz~3.2 GHz	9 kHz~2.1 GHz
Resolution Bandwidth	10 Hz~1 MHz, in 1-3-10 sequence	10 Hz~1 MHz, in 1-3-10 sequence
Displayed Average Noise Level	-161 dBm/Hz, Normalize to 1 Hz (typ.)	-161 dBm/Hz, Normalize to 1 Hz (typ.)
Phase Noise	< -98 dBc/Hz@1 GHz, 10 kHz offset	< -98 dBc/Hz@1 GHz, 10 kHz offset
Amplitude Accuracy	< 0.7 dB	< 0.7 dB
TG-SSA3000X (Opt.)	Tracking Generator Kit Free	
EMI-SSA3000X (Opt.)	EMI measurement kit	
AMK-SSA3000X (Opt.)	Advanced measurement kit	
Reff-SSA3000X (Opt.)	Reflection measurement kit	



Double the Scope at Half the Price

SDS1000X-E Series Super Phosphor Oscilloscope

- 200 MHz Bandwidth
- 1 GSa/s Real-time Sampling Rate
- True measurement and math to all of sample 14 M points
- 1 M points FFT
- Serial bus triggering and decode (Standard)

Model	SDS1202X-E
Bandwidth	200 MHz
Sampling Rate (Max.)	1 GSa/s
Channels	2+EXT
Memory Depth (Max.)	7 Mpts/CH (Dual-Channel); 14 Mpts/CH (Single-Channel)
Waveform Capture Rate (Max.)	100,000 wfms/s (normal mode), 400,000 wfms/s (sequence mode)
Trigger Type	Edge, Slope, Pulse Width, Window, Runt, Interval, Dropout, Pattern, Video

SIGLENT TECHNOLOGIES CO., LTD.

Add: Blog No.4 & No.5, Antongda Industrial Zone, 3rd Liuxian Road, Bao'an District, Shenzhen, 518101, China.
Tel: +86 755 3661 5186, Email: sales@siglent.com, Website: http://www.siglent.com/ens/.

SIGLENT®