

Digital DCDC Converters



LGA80D-00SADJJ



LGA80D-EVAL-KIT

Isolated DCDC Special Features

- Isolated DCDC converters follow the DOSA standard footprints for digital interface bricks

V _{out}	I _{out}	Input Voltage	Package size	Efficiency	Model Number
12 Vdc	26 A	48 V (36-75 V)	Eighth brick	95%	ADO300-48S12-6LI
	26 A	48 V (36-75 V)	Eighth brick	95%	ADO300-48S12B-6LI
	42 A	48 V (36-75 V)	Quarter brick	95%	ADQ500-48S12-6LI
	42 A	48 V (36-75 V)	Quarter brick	95%	ADQ500-48S12B-6LI
	58 A	48 V (40-60 V)	Quarter brick	96%	ADQ700-48S12-LI
	58 A	48 V (40-60 V)	Quarter brick	96%	ADQ700-48S12B-6LI

Non-Isolated DCDC Special Features

- Non Isolated LGA80D has dual independently controlled channels of up to 40 A per channel
- Provides current density of 160 A per Sq-Inch
- Evaluation Kit available

Output Current	Input Voltage	Output Voltage	Efficiency	Package L x W x H (mm)	Model Number
Channel 1: 40 A	7.5-14 Vdc	0.6-5 Vdc	95.5%	1" x 0.5" x 0.48" (25.4 x 12.7 x 12.2)	LGA80D-00DADJJ
Channel 2: 40 A	7.5-14 Vdc	0.6-5 Vdc	95.5%	1" x 0.5" x 0.48" (25.4 x 12.7 x 12.2)	LGA80D-00DADJJ
Total Output: 80 A	7.5-14 Vdc	0.6-5 Vdc	95.5%	1" x 0.5" x 0.48" (25.4 x 12.7 x 12.2)	LGA80D-00DADJJ

Products Inquiry:

Tel.: +91 80 4176 4537

Email: productsupport.ep@Artesyn.com