

ST25TA series NFC/RFID tags



NFC/RFID tags with ISO/IEC 14443 Type A RF interface, NDEF memory and 128-bit password protection

ST's ST25TA ICs provide the NFC Forum Type 4 Tag RF interface and built-in NDEF (NFC Data Exchange Format) message support. The embedded EEPROM memory density spans from 512 bits to 64 Kbits, covering a wide spectrum of applications including content-rich virtual business cards and smart signs. The ST25TA series delivers state-of-the-art RF performance and features a user-programmable digital CMOS (or Open Drain) output that eliminates the need for an external component to trigger the host wake-up.

KEY FEATURES

- ISO/IEC 14443 Type A
- NFC Forum Type 4 Tag
- 13.56 MHz carrier frequency
- 512-bit, 2-Kbit, 16-Kbit and 64-Kbit densities
- 56-bit unique identifier
- 128-bit password protection
- Optional 20-bit counter
- Optional RF status digital output
- 5- and 8-lead UDFPN packages
- Bumped wafer die form packages
- 25 or 50pF tuning capacitance
- 200 years data retention
- 1 million write erase cycles

Meet ST at
SmartCards Expo 2017
October 25-27, 2017

Pragati Maidan, Mathura Road, New Delhi, India

Come and
see us at our
Booth No. 21– Hall 12 A



STMicroelectronics Pvt Ltd

Plot No 1, Knowledge Park III,
Greater Noida 201308, Uttar Pradesh, India

Authorized distributors

• Arrow: Uday 9880899000 • Aela Lucky: Munish: 9717091771 • Arnet: Prakash: 9686671300
• EDOM: Om Prakash: 9910075805 • Future: Sunil: 9844640436 • Nextty: Priji: 9819794974
• Teck: Surendranath: 9810728299 • WT: Ramesh Kumar: 9008088998 • Yosun: Anurag: 9910645646

Send Enquiry to: nidhi-sehgal.kaul@st.com

www.st.com/stm25