

## Share Your Knowledge

If you are an expert in your field of electronics, why not share your knowledge with the world?



Electronics For You invites electronics professionals and industry experts to write articles on their area of expertise and interest from different perspectives

Some of the topics we want you to write about are:

- Photonics: Optics & Optoelectronics
- Automation
- Power Electronics
- Components
- Telecom

So if you have an interesting topic or original article to share, please let us know at [efyeditorial@efy.in](mailto:efyeditorial@efy.in)

*We would love to hear your good ideas too!*

**electronics**  
FOR YOU




Fig. 3: Demo for process control using Proview (Image courtesy: <https://sourceforge.net>)




Fig. 4: Table/curve component (Image courtesy: <https://sourceforge.net>)

are controlled by Trend properties. (These can be connected to analogue signals.)

**Table/curve component.** With CompCurveTab it is easy to derive the value of 'y' in a curve for a specific value of 'x.'

**Polynomial curve component.** It is similar to CompCurveTab value, but here the curve is specified with a polynomial, which means for a specific value of 'x' on the curve, the user will obtain value of 'y.'

**Xtt tree window to view specific classes.** It is a new window that dis-

plays curves both in current node and mounted node.

**Redundancy.** Proview SCADA implements a redundant system with two identical nodes: active and passive. The active node executes the PLC program, while the passive node receives the database and alarm for execution. The PLC thread in the passive node receives the packet and later inserts the data in required objects.

This complete communication is handled by `rt_redcomm` (redundancy communication).

**Classes.** As the bandwidth is limited, only the data needed for redundancy is included. For instance, description strings will not change in runtime but acquire more space in the packet. So, these would be excluded.

### Build and

**distribute.** When the build node is active, primary and secondary nodes are built individually. When distribute node is active, both the nodes are listed.

### Inference

Proview SCADA is by far one of the most successfully used open source SCADA software, which is quite popular in forums among designers. Originally developed by Swedish manufacturers, it has become a full-fledged yet low-cost solution. **EFY**